

# Capaciteitstabel SCM 40 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Indoor unit combination		Cooling capacity (kW)					Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)		Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	Min.	Standard	Max.						
1 unit	20	2.00	-	1.5	2.0	3.4	340	430	930	2.2	2.1	2.0
	25	2.50	-	1.5	2.5	3.8	340	600	1110	3.0	2.9	2.8
	35	3.50	-	1.5	3.5	4.5	340	1000	1470	4.7	4.5	4.3
2 units	20 + 20	2.00	2.00	1.7	4.0	5.9	340	800	2100	3.7	3.5	3.4
	20 + 25	1.78	2.22	1.7	4.0	5.9	340	800	2100	3.7	3.5	3.4
	20 + 35	1.45	2.55	1.7	4.0	5.9	340	800	2100	3.7	3.5	3.4
	25 + 25	2.00	2.00	1.7	4.0	5.9	340	800	2100	3.7	3.5	3.4
	25 + 35	1.67	2.33	1.7	4.0	5.9	340	800	2100	3.7	3.5	3.4

In combinatie met binnenunits anders dan SRK xxx ZSX-W

Indoor unit combination		Heating capacity (kW)					Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)		Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	Min.	Standard	Max.						
1 unit	20	3.0	-	1.0	3.0	4.5	250	680	1140	3.2	3.1	3.0
	25	3.4	-	1.0	3.4	4.9	250	790	1270	3.7	3.5	3.4
	35	4.5	-	1.0	4.5	5.4	250	1140	1470	5.3	5.1	4.8
2 units	20 + 20	2.25	2.25	1.2	4.5	6.3	250	830	1480	3.8	3.7	3.5
	20 + 25	2.00	2.50	1.2	4.5	6.3	250	830	1480	3.8	3.7	3.5
	20 + 35	1.64	2.86	1.2	4.5	6.3	250	830	1480	3.8	3.7	3.5
	25 + 25	2.25	2.25	1.2	4.5	6.3	250	830	1480	3.8	3.7	3.5
	25 + 35	1.88	2.63	1.2	4.5	6.3	250	830	1480	3.8	3.7	3.5

# Capaciteitstabel

## SCM 40 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Indoor unit combination		Cooling capacity (kW)					Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)		Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	Min.	Standard	Max.						
1 unit	20	2.00	-	1.5	2.0	3.4	340	430	930	2.2	2.1	2.0
	25	2.50	-	1.5	2.5	3.8	340	600	1110	3.0	2.9	2.8
	35	3.50	-	1.5	3.5	4.5	340	1000	1470	4.7	4.5	4.3
2 units	20 + 20	2.00	2.00	1.7	4.0	5.9	340	800	2100	3.7	3.5	3.4
	20 + 25	1.78	2.22	1.7	4.0	5.9	340	800	2100	3.7	3.5	3.4
	20 + 35	1.45	2.55	1.7	4.0	5.9	340	800	2100	3.7	3.5	3.4
	25 + 25	2.00	2.00	1.7	4.0	5.9	340	800	2100	3.7	3.5	3.4
	25 + 35	1.67	2.33	1.7	4.0	5.9	340	800	2100	3.7	3.5	3.4

Uitsluitend in combinatie met SRK xxx ZSX-W

Indoor unit combination		Heating capacity (kW)					Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)		Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	Min.	Standard	Max.						
1 unit	20	3.0	-	1.0	3.0	4.5	250	680	1140	3.2	3.1	3.0
	25	3.4	-	1.0	3.4	4.9	250	790	1270	3.7	3.5	3.4
	35	4.5	-	1.0	4.5	5.4	250	1140	1470	5.3	5.1	4.8
2 units	20 + 20	2.25	2.25	1.2	4.5	6.3	250	830	1480	3.8	3.7	3.5
	20 + 25	2.00	2.50	1.2	4.5	6.3	250	830	1480	3.8	3.7	3.5
	20 + 35	1.64	2.86	1.2	4.5	6.3	250	830	1480	3.8	3.7	3.5
	25 + 25	2.25	2.25	1.2	4.5	6.3	250	830	1480	3.8	3.7	3.5
	25 + 35	1.88	2.63	1.2	4.5	6.3	250	830	1480	3.8	3.7	3.5

# Combinatietabel

## SCM 40 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Aansluitbare binnendelen

Aantal binnenunits minimaal: 2

Aantal binnenunits maximaal: 2

Maximaal aansluitbare capaciteit: 6,0kW

Uitzonderingen: Geen

	Aansluitbaar
SRK 20 ZS-W	Ja
SRK 25 ZS-W	Ja
SRK 35 ZS-W	Ja
SRK 50 ZS-W	Nee
SRK 20 ZSX-W	Ja
SRK 25 ZSX-W	Ja
SRK 35 ZSX-W	Ja
SRK 50 ZSX-W	Nee
SRK 60 ZSX-W	Nee
SRK 71 ZR-W	Nee
FDTC 25 VH	Ja
FDTC 35 VH	Ja
FDTC 50 VH	Nee
FDTC 60 VH	Nee
FDTC 25 VF	Nee
FDTC 35 VF	Nee
FDTC 50 VF	Nee
FDTC 60 VF	Nee

	Aansluitbaar
SRR 25 ZM-W	Ja
SRR 35 ZM-W	Ja
SRR 50 ZS-W	Nee
SRR 60 ZS-W	Nee
SRR 25 ZM-S	Nee
SRR 35 ZM-S	Nee
SRR 50 ZM-S	Nee
SRR 60 ZM-S	Nee
FDUM 50 VH	Nee
FDE 50 VH	Nee
SRF 25 ZMX-S	Nee
SRF 35 ZMX-S	Nee
SRF 50 ZMX-S	Nee

# Capaciteitstabel SCM 45 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Indoor unit combination		Cooling capacity (kW)					Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)		Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	Min.	Standard	Max.						
1 unit	20	2.00	-	1.5	2.0	3.1	340	510	990	2.5	2.4	2.3
	25	2.50	-	1.5	2.5	3.4	340	710	1120	3.4	3.2	3.1
	35	3.50	-	1.5	3.5	4.1	340	1190	1570	5.5	5.3	5.0
2 units	20 + 20	2.00	2.00	1.7	4.0	5.4	340	1050	1920	4.8	4.6	4.4
	20 + 25	2.00	2.50	1.7	4.5	5.6	340	1200	2300	5.5	5.3	5.1
	20 + 35	1.64	2.86	1.7	4.5	5.6	340	1200	2300	5.5	5.3	5.1
	25 + 25	2.25	2.25	1.7	4.5	5.6	340	1200	2300	5.5	5.3	5.1
	25 + 35	1.88	2.63	1.7	4.5	5.6	340	1200	2300	5.5	5.3	5.1
	35 + 35	2.25	2.25	1.7	4.5	5.6	340	1200	2300	5.5	5.3	5.1

In combinatie met binnenunits anders dan SRK xxx ZSX-W

Indoor unit combination		Heating capacity (kW)					Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)		Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	Min.	Standard	Max.						
1 unit	20	3.00	-	1.0	3.0	3.5	250	780	940	3.7	3.5	3.4
	25	3.40	-	1.0	3.4	4.0	250	910	1120	4.3	4.1	3.9
	35	4.50	-	1.0	4.5	4.8	250	1310	1350	6.1	5.8	5.6
2 units	20 + 20	2.25	2.25	1.2	4.5	5.5	250	990	1270	4.6	4.4	4.2
	20 + 25	2.36	2.94	1.2	5.3	6.5	250	1280	1630	5.9	5.7	5.4
	20 + 35	1.93	3.37	1.2	5.3	6.5	250	1280	1630	5.9	5.7	5.4
	25 + 25	2.65	2.65	1.2	5.3	6.5	250	1280	1630	5.9	5.7	5.4
	25 + 35	2.21	3.09	1.2	5.3	6.5	250	1280	1630	5.9	5.7	5.4
	35 + 35	2.65	2.65	1.2	5.3	6.5	250	1280	1630	5.9	5.7	5.4

# Capaciteitstabel SCM 45 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Indoor unit combination		Cooling capacity (kW)					Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)		Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	Min.	Standard	Max.						
1 unit	20	2.00	-	1.5	2.0	3.4	340	430	930	2.2	2.1	2.0
	25	2.50	-	1.5	2.5	3.8	340	600	1110	3.0	2.9	2.8
	35	3.50	-	1.5	3.5	4.5	340	1000	1470	4.7	4.5	4.3
2 units	20 + 20	2.00	2.00	1.7	4.0	6.2	340	860	2100	4.0	3.8	3.7
	20 + 25	2.00	2.50	1.7	4.5	6.4	340	960	2300	4.5	4.3	4.1
	20 + 35	1.64	2.86	1.7	4.5	6.4	340	960	2300	4.5	4.3	4.1
	25 + 25	2.25	2.25	1.7	4.5	6.4	340	960	2300	4.5	4.3	4.1
	25 + 35	1.88	2.63	1.7	4.5	6.4	340	960	2300	4.5	4.3	4.1
	35 + 35	2.25	2.25	1.7	4.5	6.4	340	960	2300	4.5	4.3	4.1

Uitsluitend in combinatie met SRK xxx ZSX-W

Indoor unit combination		Heating capacity (kW)					Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)		Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	Min.	Standard	Max.						
1 unit	20	3.0	-	1.0	3.0	4.5	250	680	1140	3.2	3.1	3.0
	25	3.4	-	1.0	3.4	4.9	250	790	1270	3.7	3.5	3.4
	35	4.5	-	1.0	4.5	5.4	250	1140	1470	5.3	5.1	4.8
2 units	20 + 20	2.25	2.25	1.2	4.5	6.5	250	830	1480	3.8	3.7	3.5
	20 + 25	2.36	2.94	1.2	5.3	6.5	250	1060	1480	4.9	4.7	4.5
	20 + 35	1.93	3.37	1.2	5.3	6.5	250	1060	1480	4.9	4.7	4.5
	25 + 25	2.65	2.65	1.2	5.3	6.5	250	1060	1480	4.9	4.7	4.5
	25 + 35	2.21	3.09	1.2	5.3	6.5	250	1060	1480	4.9	4.7	4.5
	35 + 35	2.65	2.65	1.2	5.3	6.5	250	1060	1480	4.9	4.7	4.5

# Combinatietabel

## SCM 45 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Aansluitbare binnendelen

Aantal binnenunits minimaal: 2

Aantal binnenunits maximaal: 2

Maximaal aansluitbare capaciteit: 7,0kW

Uitzonderingen: Geen

	Aansluitbaar
SRK 20 ZS-W	Ja
SRK 25 ZS-W	Ja
SRK 35 ZS-W	Ja
SRK 50 ZS-W	Nee
SRK 20 ZSX-W	Ja
SRK 25 ZSX-W	Ja
SRK 35 ZSX-W	Ja
SRK 50 ZSX-W	Nee
SRK 60 ZSX-W	Nee
SRK 71 ZR-W	Nee
FDTC 25 VH	Ja
FDTC 35 VH	Ja
FDTC 50 VH	Nee
FDTC 60 VH	Nee
FDTC 25 VF	Nee
FDTC 35 VF	Nee
FDTC 50 VF	Nee
FDTC 60 VF	Nee

	Aansluitbaar
SRR 25 ZM-W	Ja
SRR 35 ZM-W	Ja
SRR 50 ZS-W	Nee
SRR 60 ZS-W	Nee
SRR 25 ZM-S	Nee
SRR 35 ZM-S	Nee
SRR 50 ZM-S	Nee
SRR 60 ZM-S	Nee
FDUM 50 VH	Nee
FDE 50 VH	Nee
SRF 25 ZMX-S	Nee
SRF 35 ZMX-S	Nee
SRF 50 ZMX-S	Nee

# Capaciteitstabel

## SCM 50 ZS-W

In combinatie met binnenunits  
anders dan SRK xxx ZSX-W

**STULZ**

CLIMATE. CUSTOMIZED.

Cooling		Cooling capacity (kW)							Power consumption(W)			Standard current(A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
1 unit	20	2.0	-	-	-	1.7	2.0	2.7	430	530	900	2.5	2.4	2.3
	25	2.5	-	-	-	1.7	2.5	3.2	430	730	1070	3.4	3.3	3.1
	35	3.5	-	-	-	1.7	3.5	3.7	430	1120	1230	5.2	4.9	4.7
	50	5.0	-	-	-	1.7	5.0	5.3	430	1710	2000	7.9	7.5	7.2
2 units	20+20	2.0	2.0	-	-	1.8	4.0	5.6	390	950	1800	4.4	4.2	4.0
	20+25	2.0	2.5	-	-	1.8	4.5	5.8	390	1110	1980	5.1	4.9	4.7
	20+35	1.8	3.2	-	-	1.8	5.0	6.3	390	1350	2150	6.2	5.9	5.7
	20+50	1.4	3.6	-	-	1.8	5.0	6.3	390	1350	2150	6.2	5.9	5.7
	25+25	2.5	2.5	-	-	1.8	5.0	6.3	390	1350	2150	6.2	5.9	5.7
	25+35	2.1	2.9	-	-	1.8	5.0	6.3	390	1350	2150	6.2	5.9	5.7
	25+50	1.7	3.3	-	-	1.8	5.0	6.3	390	1350	2150	6.2	5.9	5.7
	35+35	2.5	2.5	-	-	1.8	5.0	6.3	390	1350	2150	6.2	5.9	5.7
3 units	20+20+20	1.7	1.7	1.7	-	2.1	5.0	6.9	350	1120	2150	5.1	4.9	4.7
	20+20+25	1.5	1.5	1.9	-	2.1	5.0	6.9	350	1120	2150	5.1	4.9	4.7
	20+20+35	1.3	1.3	2.3	-	2.1	5.0	6.9	350	1120	2150	5.1	4.9	4.7
	20+25+25	1.4	1.8	1.8	-	2.1	5.0	6.9	350	1120	2150	5.1	4.9	4.7
	20+25+35	1.3	1.6	2.2	-	2.1	5.0	6.9	350	1120	2150	5.1	4.9	4.7
	25+25+25	1.7	1.7	1.7	-	2.1	5.0	6.9	350	1120	2150	5.1	4.9	4.7
	25+25+35	1.5	1.5	2.1	-	2.1	5.0	6.9	350	1120	2150	5.1	4.9	4.7

# Capaciteitstabel SCM 50 ZS-W

In combinatie met binnenunits  
anders dan SRK xxx ZSX-W

**STULZ**

CLIMATE. CUSTOMIZED.

Heating		Heating capacity (kW)							Power consumption (W)			Standard current (A)		
Indoor unit combination		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
1 unit	20	3	-	-	-	1.0	3.0	3.5	320	970	1100	4.5	4.3	4.1
	25	3.4	-	-	-	1.0	3.4	4.0	320	1140	1240	5.3	5.1	4.8
	35	4.5	-	-	-	1.0	4.5	4.8	320	1480	1490	6.9	6.6	6.3
	50	5.8	-	-	-	1.0	5.8	6.1	320	1780	2310	8.3	7.9	7.6
2 units	20+20	2.7	2.7	-	-	1.2	5.4	7.0	290	1350	2500	6.3	6.0	5.7
	20+25	2.6	3.3	-	-	1.2	5.9	7.0	290	1480	2500	6.9	6.6	6.3
	20+35	2.2	3.8	-	-	1.2	6.0	7.0	290	1500	2500	7.0	6.7	6.4
	20+50	1.7	4.3	-	-	1.2	6.0	7.0	290	1500	2500	7.0	6.7	6.4
	25+25	3.0	3.0	-	-	1.2	6.0	7.0	290	1500	2500	7.0	6.7	6.4
	25+35	2.5	3.5	-	-	1.2	6.0	7.0	290	1500	2500	7.0	6.7	6.4
	25+50	2.0	4.0	-	-	1.2	6.0	7.0	290	1500	2500	7.0	6.7	6.4
	35+35	3.0	3.0	-	-	1.2	6.0	7.0	290	1500	2500	7.0	6.7	6.4
35+50	2.5	3.5	-	-	1.2	6.0	7.0	290	1500	2500	7.0	6.7	6.4	
3 units	20+20+20	2.0	2.0	2.0	-	1.4	6.0	7.3	270	1300	2500	6.0	5.8	5.5
	20+20+25	1.8	1.8	2.3	-	1.4	6.0	7.3	270	1300	2500	6.0	5.8	5.5
	20+20+35	1.6	1.6	2.8	-	1.4	6.0	7.3	270	1300	2500	6.0	5.8	5.5
	20+25+25	1.7	2.1	2.1	-	1.4	6.0	7.3	270	1300	2500	6.0	5.8	5.5
	20+25+35	1.5	1.9	2.6	-	1.4	6.0	7.3	270	1300	2500	6.0	5.8	5.5
	25+25+25	2.0	2.0	2.0	-	1.4	6.0	7.3	270	1300	2500	6.0	5.8	5.5
	25+25+35	1.8	1.8	2.5	-	1.4	6.0	7.3	270	1300	2500	6.0	5.8	5.5



# Capaciteitstabel

## SCM 50 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Uitsluitend in combinatie met SRK xxx ZSX-W

Cooling		Cooling capacity (kW)							Power consumption(W)			Standard current(A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
1 unit	20	2.0	-	-	-	1.7	2.0	2.8	430	500	950	2.4	2.3	2.2
	25	2.5	-	-	-	1.7	2.5	3.4	430	680	1070	3.2	3.1	3.0
	35	3.5	-	-	-	1.7	3.5	3.9	430	1010	1230	4.7	4.5	4.3
	50	5.0	-	-	-	1.7	5.0	5.5	430	1530	2000	7.0	6.7	6.4
2 units	20+20	2.0	2.0	-	-	1.8	4.0	5.7	390	750	1750	3.5	3.3	3.2
	20+25	2.0	2.5	-	-	1.8	4.5	5.9	390	990	1910	4.6	4.4	4.2
	20+35	1.8	3.2	-	-	1.8	5.0	6.5	390	1110	2150	5.1	4.9	4.7
	20+50	1.4	3.6	-	-	1.8	5.0	6.5	390	1110	2150	5.1	4.9	4.7
	25+25	2.5	2.5	-	-	1.8	5.0	6.5	390	1110	2150	5.1	4.9	4.7
	25+35	2.1	2.9	-	-	1.8	5.0	6.5	390	1110	2150	5.1	4.9	4.7
	25+50	1.7	3.3	-	-	1.8	5.0	6.5	390	1110	2150	5.1	4.9	4.7
	35+35	2.5	2.5	-	-	1.8	5.0	6.5	390	1110	2150	5.1	4.9	4.7
	35+50	2.1	2.9	-	-	1.8	5.0	6.5	390	1110	2150	5.1	4.9	4.7
3 units	20+20+20	1.7	1.7	1.7	-	2.1	5.0	7.1	350	1020	2150	4.7	4.5	4.3
	20+20+25	1.5	1.5	1.9	-	2.1	5.0	7.1	350	1020	2150	4.7	4.5	4.3
	20+20+35	1.3	1.3	2.3	-	2.1	5.0	7.1	350	1020	2150	4.7	4.5	4.3
	20+25+25	1.4	1.8	1.8	-	2.1	5.0	7.1	350	1020	2150	4.7	4.5	4.3
	20+25+35	1.3	1.6	2.2	-	2.1	5.0	7.1	350	1020	2150	4.7	4.5	4.3
	25+25+5	1.7	1.7	1.7	-	2.1	5.0	7.1	350	1020	2150	4.7	4.5	4.3
	25+25+35	1.5	1.5	2.1	-	2.1	5.0	7.1	350	1020	2150	4.7	4.5	4.3

# Capaciteitstabel SCM 50 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Uitsluitend in combinatie met SRK xxx ZSX-W

Heating		Heating capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
1 unit	20	3	-	-	-	1.0	3.0	3.7	320	780	1100	3.6	3.5	3.3
	25	3.4	-	-	-	1.0	3.4	4.2	320	950	1240	4.4	4.2	4.0
	35	4.5	-	-	-	1.0	4.5	5.0	320	1270	1490	5.9	5.6	5.4
	50	5.8	-	-	-	1.0	5.8	6.5	320	1710	2310	7.9	7.6	7.3
2 units	20+20	2.7	2.7	-	-	1.2	5.4	7.3	290	1050	2500	4.9	4.7	4.5
	20+25	2.6	3.3	-	-	1.2	5.9	7.3	290	1180	2500	5.5	5.2	5.0
	20+35	2.2	3.8	-	-	1.2	6.0	7.3	290	1200	2500	5.6	5.3	5.1
	20+50	1.7	4.3	-	-	1.2	6.0	7.3	290	1200	2500	5.6	5.3	5.1
	25+25	3.0	3.0	-	-	1.2	6.0	7.3	290	1200	2500	5.6	5.3	5.1
	25+35	2.5	3.5	-	-	1.2	6.0	7.3	290	1200	2500	5.6	5.3	5.1
	25+50	2.0	4.0	-	-	1.2	6.0	7.3	290	1200	2500	5.6	5.3	5.1
	35+35	3.0	3.0	-	-	1.2	6.0	7.3	290	1200	2500	5.6	5.3	5.1
35+50	2.5	3.5	-	-	1.2	6.0	7.3	290	1200	2500	5.6	5.3	5.1	
3 units	20+20+20	2.57	2.57	2.57	-	1.4	6.0	7.5	270	1160	2500	5.4	5.1	4.9
	20+20+25	2.46	2.46	3.08	-	1.4	6.0	7.5	270	1160	2500	5.4	5.1	4.9
	20+20+35	2.24	2.24	3.92	-	1.4	6.0	7.5	270	1160	2500	5.4	5.1	4.9
	20+25+25	2.34	2.93	2.93	-	1.4	6.0	7.5	270	1160	2500	5.4	5.1	4.9
	20+25+35	2.10	2.63	3.68	-	1.4	6.0	7.5	270	1160	2500	5.4	5.1	4.9
	25+25+5	2.80	2.80	2.80	-	1.4	6.0	7.5	270	1160	2500	5.4	5.1	4.9
	25+25+35	2.47	2.47	3.46	-	1.4	6.0	7.5	270	1160	2500	5.4	5.1	4.9

# Combinatietabel

## SCM 50 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Aansluitbare binnendelen

Aantal binnenunits minimaal: 2

Aantal binnenunits maximaal: 3

Maximaal aansluitbare capaciteit: 8,5kW

Uitzonderingen: Geen

	Aansluitbaar
SRK 20 ZS-W	Ja
SRK 25 ZS-W	Ja
SRK 35 ZS-W	Ja
SRK 50 ZS-W	Ja
SRK 20 ZSX-W	Ja
SRK 25 ZSX-W	Ja
SRK 35 ZSX-W	Ja
SRK 50 ZSX-W	Ja
SRK 60 ZSX-W	Nee
SRK 71 ZR-W	Nee
FDTC 25 VH	Ja
FDTC 35 VH	Ja
FDTC 50 VH	Ja
FDTC 60 VH	Nee
FDTC 25 VF	Nee
FDTC 35 VF	Nee
FDTC 50 VF	Nee
FDTC 60 VF	Nee

	Aansluitbaar
SRR 25 ZM-W	Ja
SRR 35 ZM-W	Ja
SRR 50 ZS-W	Ja
SRR 60 ZS-W	Nee
SRR 25 ZM-S	Nee
SRR 35 ZM-S	Nee
SRR 50 ZM-S	Nee
SRR 60 ZM-S	Nee
FDUM 50 VH	Ja
FDE 50 VH	Ja
SRF 25 ZMX-S	Nee
SRF 35 ZMX-S	Nee
SRF 50 ZMX-S	Nee

# Capaciteitstabel

## SCM 60 ZS-W

In combinatie met binnenunits  
anders dan SRK xxx ZSX-W

**STULZ**

CLIMATE. CUSTOMIZED.

Cooling		Cooling capacity (kW)							Power consumption(W)			Standard current(A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
1 unit	20	2.0	-	-	-	1.7	2.0	2.7	430	570	950	2.7	2.6	2.5
	25	2.5	-	-	-	1.7	2.5	3.2	430	760	1080	3.6	3.4	3.3
	35	3.5	-	-	-	1.7	3.5	3.7	430	1150	1240	5.3	5.1	4.9
	50	5.0	-	-	-	1.7	5.0	5.8	430	1860	2100	8.5	8.2	7.8
	60	6.0	-	-	-	1.7	6.0	6.1	430	2140	2280	9.8	9.4	9.0
2 units	20+20	2.0	2.0	-	-	1.8	4.0	5.6	390	800	1750	3.7	3.5	3.4
	20+25	2.0	2.5	-	-	1.8	4.5	5.8	390	1050	1910	4.8	4.6	4.4
	20+35	2.0	3.5	-	-	1.8	5.5	6.1	390	1620	2110	7.4	7.1	6.8
	20+50	1.7	4.3	-	-	1.8	6.0	6.7	390	1930	2280	8.9	8.5	8.1
	20+60	1.5	4.5	-	-	1.8	6.0	6.7	390	1930	2280	8.9	8.5	8.1
	25+25	2.5	2.5	-	-	1.8	5.0	6.1	390	1340	2110	6.2	5.9	5.6
	25+35	2.5	3.5	-	-	1.8	6.0	6.7	390	1930	2280	8.9	8.5	8.1
	25+50	2.0	4.0	-	-	1.8	6.0	6.7	390	1930	2280	8.9	8.5	8.1
	25+60	1.8	4.2	-	-	1.8	6.0	6.7	390	1930	2280	8.9	8.5	8.1
	35+35	3.0	3.0	-	-	1.8	6.0	6.7	390	1930	2280	8.9	8.5	8.1
	35+50	2.5	3.5	-	-	1.8	6.0	6.7	390	1930	2280	8.9	8.5	8.1
	35+60	2.2	3.8	-	-	1.8	6.0	6.7	390	1930	2280	8.9	8.5	8.1
	50+50	3.0	3.0	-	-	1.8	6.0	6.7	390	1930	2280	8.9	8.5	8.1
50+60	2.7	3.3	-	-	1.8	6.0	6.7	390	1930	2280	8.9	8.5	8.1	

Met 3 units op  
volgende pagina!

# Capaciteitstabel

## SCM 60 ZS-W

In combinatie met binnenunits  
anders dan SRK xxx ZSX-W

**STULZ**

CLIMATE. CUSTOMIZED.

Cooling		Cooling capacity (kW)							Power consumption(W)			Standard current(A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
Indoor unit combination		A	B	C	D	Min.	Standard	Max.						
		3 units	20+20+20	2.0	2.0	2.0	-	2.1	6.0	7.3	350	1430	2280	6.6
20+20+25	1.8		1.8	2.3	-	2.1	6.0	7.3	350	1430	2280	6.6	6.3	6.0
20+20+35	1.6		1.6	2.8	-	2.1	6.0	7.3	350	1430	2280	6.6	6.3	6.0
20+20+50	1.3		1.3	3.3	-	2.1	6.0	7.3	350	1430	2280	6.6	6.3	6.0
20+20+60	1.2		1.2	3.6	-	2.1	6.0	7.3	350	1430	2280	6.6	6.3	6.0
20+25+25	1.7		2.1	2.1	-	2.1	6.0	7.3	350	1430	2280	6.6	6.3	6.0
20+25+35	1.5		1.9	2.6	-	2.1	6.0	7.3	350	1430	2280	6.6	6.3	6.0
20+25+50	1.3		1.6	3.2	-	2.1	6.0	7.3	350	1430	2280	6.6	6.3	6.0
20+25+60	1.1		1.4	3.4	-	2.1	6.0	7.3	350	1430	2280	6.6	6.3	6.0
20+35+35	1.3		2.3	2.3	-	2.1	6.0	7.3	350	1430	2280	6.6	6.3	6.0
20+35+50	1.1		2.0	2.9	-	2.1	6.0	7.3	350	1430	2280	6.6	6.3	6.0
25+25+25	2.0		2.0	2.0	-	2.1	6.0	7.3	350	1430	2280	6.6	6.3	6.0
25+25+35	1.8		1.8	2.5	-	2.1	6.0	7.3	350	1430	2280	6.6	6.3	6.0
25+25+50	1.5		1.5	3.0	-	2.1	6.0	7.3	350	1430	2280	6.6	6.3	6.0
25+25+60	1.4		1.4	3.3	-	2.1	6.0	7.3	350	1430	2280	6.6	6.3	6.0
25+35+35	1.6		2.2	2.2	-	2.1	6.0	7.3	350	1430	2280	6.6	6.3	6.0
25+35+50	1.4	1.9	2.7	-	2.1	6.0	7.3	350	1430	2280	6.6	6.3	6.0	
35+35+35	2.0	2.0	2.0	-	2.1	6.0	7.3	350	1430	2280	6.6	6.3	6.0	

# Capaciteitstabel SCM 60 ZS-W

In combinatie met binnenunits  
anders dan SRK xxx ZSX-W

**STULZ**

CLIMATE. CUSTOMIZED.

Heating		Heating capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
1 unit	20	3.0	-	-	-	1.0	3.0	3.5	320	970	1330	4.5	4.3	4.1
	25	3.4	-	-	-	1.0	3.4	4.0	320	1140	1510	5.3	5.1	4.8
	35	4.5	-	-	-	1.0	4.5	4.8	320	1480	1790	6.9	6.6	6.3
	50	5.8	-	-	-	1.0	5.8	6.1	320	1910	2310	8.9	8.5	8.1
	60	6.8	-	-	-	1.0	6.8	7.0	320	2200	2660	10.2	9.8	9.4
2 units	20+20	2.7	2.7	-	-	1.2	5.4	7.0	290	1250	2100	5.8	5.5	5.3
	20+25	2.6	3.3	-	-	1.2	5.9	7.2	290	1380	2550	6.4	6.1	5.9
	20+35	2.4	4.2	-	-	1.2	6.6	7.3	290	1560	2800	7.2	6.9	6.6
	20+50	1.9	4.9	-	-	1.2	6.8	7.3	290	1640	2800	7.6	7.3	7.0
	20+60	1.7	5.1	-	-	1.2	6.8	7.3	290	1640	2800	7.6	7.3	7.0
	25+25	3.2	3.2	-	-	1.2	6.4	7.3	290	1510	2800	7.0	6.7	6.4
	25+35	2.8	4.0	-	-	1.2	6.8	7.3	290	1640	2800	7.6	7.3	7.0
	25+50	2.3	4.5	-	-	1.2	6.8	7.3	290	1640	2800	7.6	7.3	7.0
	25+60	2.0	4.8	-	-	1.2	6.8	7.3	290	1640	2800	7.6	7.3	7.0
	35+35	3.4	3.4	-	-	1.2	6.8	7.3	290	1640	2800	7.6	7.3	7.0
	35+50	2.8	4.0	-	-	1.2	6.8	7.3	290	1640	2800	7.6	7.3	7.0
	35+60	2.5	4.3	-	-	1.2	6.8	7.3	290	1640	2800	7.6	7.3	7.0
	50+50	3.4	3.4	-	-	1.2	6.8	7.3	290	1640	2800	7.6	7.3	7.0
50+60	3.1	3.7	-	-	1.2	6.8	7.3	290	1640	2800	7.6	7.3	7.0	

Met 3 units op  
volgende pagina!

# Capaciteitstabel SCM 60 ZS-W

In combinatie met binnenunits  
anders dan SRK xxx ZSX-W

**STULZ**

CLIMATE. CUSTOMIZED.

Heating		Heating capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
3 units	20+20+20	2.3	2.3	2.3	-	1.4	6.8	7.6	270	1500	2800	7.0	6.7	6.4
	20+20+25	2.1	2.1	2.6	-	1.4	6.8	7.6	270	1500	2800	7.0	6.7	6.4
	20+20+35	1.8	1.8	3.2	-	1.4	6.8	7.6	270	1500	2800	7.0	6.7	6.4
	20+20+50	1.5	1.5	3.8	-	1.4	6.8	7.6	270	1500	2800	7.0	6.7	6.4
	20+20+60	1.4	1.4	4.1	-	1.4	6.8	7.6	270	1500	2800	7.0	6.7	6.4
	20+25+25	1.9	2.4	2.4	-	1.4	6.8	7.6	270	1500	2800	7.0	6.7	6.4
	20+25+35	1.7	2.1	3.0	-	1.4	6.8	7.6	270	1500	2800	7.0	6.7	6.4
	20+25+50	1.4	1.8	3.6	-	1.4	6.8	7.6	270	1500	2800	7.0	6.7	6.4
	20+25+60	1.3	1.6	3.9	-	1.4	6.8	7.6	270	1500	2800	7.0	6.7	6.4
	20+35+35	1.5	2.6	2.6	-	1.4	6.8	7.6	270	1500	2800	7.0	6.7	6.4
	20+35+50	1.3	2.3	3.2	-	1.4	6.8	7.6	270	1500	2800	7.0	6.7	6.4
	25+25+25	2.3	2.3	2.3	-	1.4	6.8	7.6	270	1500	2800	7.0	6.7	6.4
	25+25+35	2.0	2.0	2.8	-	1.4	6.8	7.6	270	1500	2800	7.0	6.7	6.4
	25+25+50	1.7	1.7	3.4	-	1.4	6.8	7.6	270	1500	2800	7.0	6.7	6.4
	25+25+60	1.5	1.5	3.7	-	1.4	6.8	7.6	270	1500	2800	7.0	6.7	6.4
25+35+35	1.8	2.5	2.5	-	1.4	6.8	7.6	270	1500	2800	7.0	6.7	6.4	
25+35+50	1.5	2.2	3.1	-	1.4	6.8	7.6	270	1500	2800	7.0	6.7	6.4	
35+35+35	2.3	2.3	2.3	-	1.4	6.8	7.6	270	1500	2800	7.0	6.7	6.4	

# Capaciteitstabel SCM 60 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Uitsluitend in combinatie met SRK xxx ZSX-W

Cooling		Cooling capacity (kW)							Power consumption(W)			Standard current(A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
1 unit	20	2.0	-	-	-	1.7	2.0	2.8	430	500	950	2.4	2.3	2.2
	25	2.5	-	-	-	1.7	2.5	3.4	430	680	1080	3.2	3.1	3.0
	35	3.5	-	-	-	1.7	3.5	3.9	430	1010	1240	4.7	4.5	4.3
	50	5.0	-	-	-	1.7	5.0	6.1	430	1530	2100	7.0	6.7	6.4
	60	6.0	-	-	-	1.7	6.0	6.3	430	1880	2280	8.6	8.3	7.9
2 units	20+20	2.0	2.0	-	-	1.8	4.0	5.7	390	750	1750	3.5	3.3	3.2
	20+25	2.0	2.5	-	-	1.8	4.5	5.9	390	990	1910	4.6	4.4	4.2
	20+35	2.0	3.5	-	-	1.8	5.5	6.7	390	1320	2200	6.1	5.8	5.6
	20+50	1.7	4.3	-	-	1.8	6.0	6.9	390	1560	2280	7.2	6.9	6.6
	20+60	1.5	4.5	-	-	1.8	6.0	6.9	390	1560	2280	7.2	6.9	6.6
	25+25	2.5	2.5	-	-	1.8	5.0	6.5	390	1110	2150	5.1	4.9	4.7
	25+35	2.5	3.5	-	-	1.8	6.0	6.9	390	1560	2280	7.2	6.9	6.6
	25+50	2.0	4.0	-	-	1.8	6.0	6.9	390	1560	2280	7.2	6.9	6.6
	25+60	1.8	4.2	-	-	1.8	6.0	6.9	390	1560	2280	7.2	6.9	6.6
	35+35	3.0	3.0	-	-	1.8	6.0	6.9	390	1560	2280	7.2	6.9	6.6
	35+50	2.5	3.5	-	-	1.8	6.0	6.9	390	1560	2280	7.2	6.9	6.6
	35+60	2.2	3.8	-	-	1.8	6.0	6.9	390	1560	2280	7.2	6.9	6.6
	50+50	3.0	3.0	-	-	1.8	6.0	6.9	390	1560	2280	7.2	6.9	6.6
50+60	2.7	3.3	-	-	1.8	6.0	6.9	390	1560	2280	7.2	6.9	6.6	

Met 3 units op  
volgende pagina!



# Capaciteitstabel

## SCM 60 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Uitsluitend in combinatie met SRK xxx ZSX-W

Cooling		Cooling capacity (kW)							Power consumption(W)			Standard current(A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
3 units	20+20+20	2.0	2.0	2.0	-	2.1	6.0	7.5	350	1320	2280	6.1	5.8	5.6
	20+20+25	1.8	1.8	2.3	-	2.1	6.0	7.5	350	1320	2280	6.1	5.8	5.6
	20+20+35	1.6	1.6	2.8	-	2.1	6.0	7.5	350	1320	2280	6.1	5.8	5.6
	20+20+50	1.3	1.3	3.3	-	2.1	6.0	7.5	350	1320	2280	6.1	5.8	5.6
	20+20+60	1.2	1.2	3.6	-	2.1	6.0	7.5	350	1320	2280	6.1	5.8	5.6
	20+25+25	1.7	2.1	2.1	-	2.1	6.0	7.5	350	1320	2280	6.1	5.8	5.6
	20+25+35	1.5	1.9	2.6	-	2.1	6.0	7.5	350	1320	2280	6.1	5.8	5.6
	20+25+50	1.3	1.6	3.2	-	2.1	6.0	7.5	350	1320	2280	6.1	5.8	5.6
	20+25+60	1.1	1.4	3.4	-	2.1	6.0	7.5	350	1320	2280	6.1	5.8	5.6
	20+35+35	1.3	2.3	2.3	-	2.1	6.0	7.5	350	1320	2280	6.1	5.8	5.6
	20+35+50	1.1	2.0	2.9	-	2.1	6.0	7.5	350	1320	2280	6.1	5.8	5.6
	25+25+25	2.0	2.0	2.0	-	2.1	6.0	7.5	350	1320	2280	6.1	5.8	5.6
	25+25+35	1.8	1.8	2.5	-	2.1	6.0	7.5	350	1320	2280	6.1	5.8	5.6
	25+25+50	1.5	1.5	3.0	-	2.1	6.0	7.5	350	1320	2280	6.1	5.8	5.6
	25+25+60	1.4	1.4	3.3	-	2.1	6.0	7.5	350	1320	2280	6.1	5.8	5.6
25+35+35	1.6	2.2	2.2	-	2.1	6.0	7.5	350	1320	2280	6.1	5.8	5.6	
25+35+50	1.4	1.9	2.7	-	2.1	6.0	7.5	350	1320	2280	6.1	5.8	5.6	
35+35+35	2.0	2.0	2.0	-	2.1	6.0	7.5	350	1320	2280	6.1	5.8	5.6	

# Capaciteitstabel SCM 60 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Uitsluitend in combinatie met SRK xxx ZSX-W

Heating		Heating capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
1 unit	20	3.0	-	-	-	1.0	3.0	3.7	320	780	1100	3.6	3.5	3.3
	25	3.4	-	-	-	1.0	3.4	4.2	320	950	1240	4.4	4.2	4.0
	35	4.5	-	-	-	1.0	4.5	5.0	320	1270	1490	5.9	5.6	5.4
	50	5.8	-	-	-	1.0	5.8	6.5	320	1710	2310	7.9	7.6	7.3
	60	6.8	-	-	-	1.0	6.8	7.3	320	2040	2660	9.5	9.1	8.7
2 units	20+20	2.7	2.7	-	-	1.2	5.4	7.3	290	1050	2100	4.9	4.7	4.5
	20+25	2.6	3.3	-	-	1.2	5.9	7.5	290	1180	2550	5.5	5.2	5.0
	20+35	2.4	4.2	-	-	1.2	6.6	7.6	290	1360	2800	6.3	6.0	5.8
	20+50	1.9	4.9	-	-	1.2	6.8	7.6	290	1440	2800	6.7	6.4	6.1
	20+60	1.7	5.1	-	-	1.2	6.8	7.6	290	1440	2800	6.7	6.4	6.1
	25+25	3.2	3.2	-	-	1.2	6.4	7.6	290	1310	2800	6.1	5.8	5.6
	25+35	2.8	4.0	-	-	1.2	6.8	7.6	290	1440	2800	6.7	6.4	6.1
	25+50	2.3	4.5	-	-	1.2	6.8	7.6	290	1440	2800	6.7	6.4	6.1
	25+60	2.0	4.8	-	-	1.2	6.8	7.6	290	1440	2800	6.7	6.4	6.1
	35+35	3.4	3.4	-	-	1.2	6.8	7.6	290	1440	2800	6.7	6.4	6.1
	35+50	2.8	4.0	-	-	1.2	6.8	7.6	290	1440	2800	6.7	6.4	6.1
	35+60	2.5	4.3	-	-	1.2	6.8	7.6	290	1440	2800	6.7	6.4	6.1
	50+50	3.4	3.4	-	-	1.2	6.8	7.6	290	1440	2800	6.7	6.4	6.1
50+60	3.1	3.7	-	-	1.2	6.8	7.6	290	1440	2800	6.7	6.4	6.1	

Met 3 units op  
volgende pagina!

# Capaciteitstabel SCM 60 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Uitsluitend in combinatie met SRK xxx ZSX-W

Heating		Heating capacity (kW)							Power consumption (W)			Standard current (A)		
Indoor unit combination		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
3 units	20+20+20	2.3	2.3	2.3	-	1.4	6.8	7.8	270	1400	2800	6.5	6.2	6.0
	20+20+25	2.1	2.1	2.6	-	1.4	6.8	7.8	270	1400	2800	6.5	6.2	6.0
	20+20+35	1.8	1.8	3.2	-	1.4	6.8	7.8	270	1400	2800	6.5	6.2	6.0
	20+20+50	1.5	1.5	3.8	-	1.4	6.8	7.8	270	1400	2800	6.5	6.2	6.0
	20+20+60	1.4	1.4	4.1	-	1.4	6.8	7.8	270	1400	2800	6.5	6.2	6.0
	20+25+25	1.9	2.4	2.4	-	1.4	6.8	7.8	270	1400	2800	6.5	6.2	6.0
	20+25+35	1.7	2.1	3.0	-	1.4	6.8	7.8	270	1400	2800	6.5	6.2	6.0
	20+25+50	1.4	1.8	3.6	-	1.4	6.8	7.8	270	1400	2800	6.5	6.2	6.0
	20+25+60	1.3	1.6	3.9	-	1.4	6.8	7.8	270	1400	2800	6.5	6.2	6.0
	20+35+35	1.5	2.6	2.6	-	1.4	6.8	7.8	270	1400	2800	6.5	6.2	6.0
	20+35+50	1.3	2.3	3.2	-	1.4	6.8	7.8	270	1400	2800	6.5	6.2	6.0
	25+25+25	2.3	2.3	2.3	-	1.4	6.8	7.8	270	1400	2800	6.5	6.2	6.0
	25+25+35	2.0	2.0	2.8	-	1.4	6.8	7.8	270	1400	2800	6.5	6.2	6.0
	25+25+50	1.7	1.7	3.4	-	1.4	6.8	7.8	270	1400	2800	6.5	6.2	6.0
	25+25+60	1.5	1.5	3.7	-	1.4	6.8	7.8	270	1400	2800	6.5	6.2	6.0
25+35+35	1.8	2.5	2.5	-	1.4	6.8	7.8	270	1400	2800	6.5	6.2	6.0	
25+35+50	1.5	2.2	3.1	-	1.4	6.8	7.8	270	1400	2800	6.5	6.2	6.0	
35+35+35	2.3	2.3	2.3	-	1.4	6.8	7.8	270	1400	2800	6.5	6.2	6.0	

# Combinatietabel

## SCM 60 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Aansluitbare binnendelen

Aantal binnenunits minimaal: 2

Aantal binnenunits maximaal: 3

Maximaal aansluitbare capaciteit: 11,0kW

Uitzonderingen: Geen

	Aansluitbaar
SRK 20 ZS-W	Ja
SRK 25 ZS-W	Ja
SRK 35 ZS-W	Ja
SRK 50 ZS-W	Ja
SRK 20 ZSX-W	Ja
SRK 25 ZSX-W	Ja
SRK 35 ZSX-W	Ja
SRK 50 ZSX-W	Ja
SRK 60 ZSX-W	Ja
SRK 71 ZR-W	Nee
FDTC 25 VH	Ja
FDTC 35 VH	Ja
FDTC 50 VH	Ja
FDTC 60 VH	Ja
FDTC 25 VF	Nee
FDTC 35 VF	Nee
FDTC 50 VF	Nee
FDTC 60 VF	Nee

	Aansluitbaar
SRR 25 ZM-W	Ja
SRR 35 ZM-W	Ja
SRR 50 ZS-W	Ja
SRR 60 ZS-W	Ja
SRR 25 ZM-S	Nee
SRR 35 ZM-S	Nee
SRR 50 ZM-S	Nee
SRR 60 ZM-S	Nee
FDUM 50 VH	Ja
FDE 50 VH	Ja
SRF 25 ZMX-S	Nee
SRF 35 ZMX-S	Nee
SRF 50 ZMX-S	Nee

# Capaciteitstabel SCM 71 ZS-W

In combinatie met binnenunits  
anders dan SRK xxx ZSX-W

**STULZ**

CLIMATE. CUSTOMIZED.

Indoor unit combination		Cooling capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
1 unit	20	2.0	-	-	-	1.8	2.0	2.7	480	530	950	2.5	2.4	2.3
	25	2.5	-	-	-	1.8	2.5	3.2	480	730	1080	3.5	3.3	3.2
	35	3.5	-	-	-	1.8	3.5	3.7	480	1120	1240	5.2	5.0	4.8
	50	5.0	-	-	-	1.8	5.0	5.8	480	1710	2100	7.9	7.5	7.2
	60	6.0	-	-	-	1.8	6.0	6.7	480	2140	2700	9.8	9.4	9.0
	71	7.1	-	-	-	1.8	7.1	7.2	480	2430	2830	11.2	10.7	10.2
2 units	20 + 20	2.00	2.00	-	-	3.0	4.0	5.8	550	930	1910	4.4	4.2	4.0
	20 + 25	2.00	2.50	-	-	3.0	4.5	6.1	550	1170	2060	5.5	5.2	5.0
	20 + 35	2.00	3.50	-	-	3.0	5.5	6.6	550	1590	2320	7.3	7.0	6.7
	20 + 50	2.03	5.07	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	20 + 60	1.78	5.33	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	20 + 71	1.56	5.54	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	25 + 25	2.50	2.50	-	-	3.0	5.0	6.5	550	1360	2270	6.3	6.0	5.8
	25 + 35	2.46	3.44	-	-	3.0	5.9	6.8	550	1780	2470	8.2	7.8	7.5
	25 + 50	2.37	4.73	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	25 + 60	2.09	5.01	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	25 + 71	1.85	5.25	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	35 + 35	3.55	3.55	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	35 + 50	2.92	4.18	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	35 + 60	2.62	4.48	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	35 + 71	2.34	4.76	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	50 + 50	3.55	3.55	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	50 + 60	3.23	3.87	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	50 + 71	2.93	4.17	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
60 + 60	3.55	3.55	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8	

Met 3/4 units op  
volgende pagina's!

# Capaciteitstabel SCM 71 ZS-W

In combinatie met binnenunits  
anders dan SRK xxx ZSX-W

**STULZ**

CLIMATE. CUSTOMIZED.

Cooling	Cooling capacity (kW)								Power consumption(W)			Standard current(A)		
	Indoor unit combination	Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
3 units	20 + 20 + 20	2.00	2.00	2.00	-	3.7	6.0	7.8	670	1440	2750	6.6	6.4	6.1
	20 + 20 + 25	2.00	2.00	2.50	-	3.7	6.5	7.8	670	1630	2750	7.5	7.2	6.9
	20 + 20 + 35	1.89	1.89	3.31	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 20 + 50	1.58	1.58	3.94	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 20 + 60	1.42	1.42	4.26	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 20 + 71	1.28	1.28	4.54	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 25 + 25	2.03	2.54	2.54	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 25 + 35	1.78	2.22	3.11	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 25 + 50	1.49	1.87	3.74	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 25 + 60	1.35	1.69	4.06	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 25 + 71	1.22	1.53	4.35	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 35 + 35	1.58	2.76	2.76	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 35 + 50	1.35	2.37	3.38	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 35 + 60	1.23	2.16	3.70	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 35 + 71	1.13	1.97	4.00	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 50 + 50	1.18	2.96	2.96	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	25 + 25 + 25	2.37	2.37	2.37	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	25 + 25 + 35	2.09	2.09	2.92	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	25 + 25 + 50	1.78	1.78	3.55	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	25 + 25 + 60	1.61	1.61	3.87	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	25 + 25 + 71	1.47	1.47	4.17	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	25 + 35 + 35	1.87	2.62	2.62	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	25 + 35 + 50	1.61	2.26	3.23	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	25 + 35 + 60	1.48	2.07	3.55	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	25 + 50 + 50	1.42	2.84	2.84	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	35 + 35 + 35	2.37	2.37	2.37	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	35 + 35 + 50	2.07	2.07	2.96	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9

Met 4 units op  
volgende pagina!

# Capaciteitstabel

## SCM 71 ZS-W

In combinatie met binnenunits  
anders dan SRK xxx ZSX-W

**STULZ**

CLIMATE. CUSTOMIZED.

Indoor unit combination		Cooling capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
4 units	20 + 20 + 20 + 20	1.78	1.78	1.78	1.78	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 20 + 20 + 25	1.67	1.67	1.67	2.09	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 20 + 20 + 35	1.49	1.49	1.49	2.62	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 20 + 20 + 50	1.29	1.29	1.29	3.23	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 20 + 20 + 60	1.18	1.18	1.18	3.55	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 20 + 25 + 25	1.58	1.58	1.97	1.97	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 20 + 25 + 35	1.42	1.42	1.78	2.49	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 20 + 25 + 50	1.23	1.23	1.54	3.09	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 20 + 25 + 60	1.14	1.14	1.42	3.41	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 20 + 35 + 35	1.29	1.29	2.26	2.26	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 20 + 35 + 50	1.14	1.14	1.99	2.84	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 25 + 25 + 25	1.49	1.87	1.87	1.87	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 25 + 25 + 35	1.35	1.69	1.69	2.37	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 25 + 25 + 50	1.18	1.48	1.48	2.96	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 25 + 35 + 35	1.23	1.54	2.16	2.16	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 35 + 35 + 35	1.14	1.99	1.99	1.99	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
25 + 25 + 25 + 25	1.78	1.78	1.78	1.78	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5	
25 + 25 + 25 + 35	1.61	1.61	1.61	2.26	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5	
25 + 25 + 25 + 50	1.42	1.42	1.42	2.84	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5	
25 + 25 + 35 + 35	1.48	1.48	2.07	2.07	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5	

# Capaciteitstabel SCM 71 ZS-W

In combinatie met binnenunits  
anders dan SRK xxx ZSX-W

**STULZ**

CLIMATE. CUSTOMIZED.

Indoor unit combination		Heating capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
1 unit	20	3.0	-	-	-	1.1	3.0	3.5	390	1060	1330	5.0	4.8	4.6
	25	3.4	-	-	-	1.1	3.4	4.0	390	1220	1510	5.7	5.5	5.2
	35	4.5	-	-	-	1.1	4.5	4.8	390	1510	1790	7.0	6.7	6.4
	50	5.8	-	-	-	1.1	5.8	6.2	390	1950	2310	9.0	8.7	8.3
	60	6.8	-	-	-	1.1	6.8	7.1	390	2240	2660	10.4	9.9	9.5
	71	8.0	-	-	-	1.1	8.0	8.1	390	2740	3000	12.7	12.2	11.6
2 units	20 + 20	2.70	2.70	-	-	1.5	5.4	7.0	350	1370	1870	6.4	6.1	5.9
	20 + 25	2.62	3.28	-	-	1.5	5.9	7.3	350	1560	2130	7.3	6.9	6.7
	20 + 35	2.51	4.39	-	-	1.5	6.9	7.9	350	1950	2650	9.0	8.7	8.3
	20 + 50	2.46	6.14	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	20 + 60	2.15	6.45	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	20 + 71	1.89	6.71	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	25 + 25	3.20	3.20	-	-	1.5	6.4	7.7	350	1740	2480	8.1	7.7	7.4
	25 + 35	3.08	4.32	-	-	1.5	7.4	8.2	350	2130	2910	9.9	9.4	9.1
	25 + 50	2.87	5.73	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	25 + 60	2.53	6.07	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	25 + 71	2.24	6.36	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	35 + 35	4.30	4.30	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	35 + 50	3.54	5.06	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	35 + 60	3.17	5.43	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	35 + 71	2.84	5.76	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	50 + 50	4.30	4.30	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	50 + 60	3.91	4.69	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	50 + 71	3.55	5.05	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
60 + 60	4.30	4.30	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5	

Met 3/4 units op  
volgende pagina's!



# Capaciteitstabel SCM 71 ZS-W

In combinatie met binnenunits  
anders dan SRK xxx ZSX-W

**STULZ**

CLIMATE. CUSTOMIZED.

Indoor unit combination		Heating capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
3 units	20 + 20 + 20	2.57	2.57	2.57	-	1.6	7.7	8.9	370	1870	3000	8.7	8.3	8.0
	20 + 20 + 25	2.46	2.46	3.08	-	1.6	8.0	8.9	370	1970	3000	9.1	8.7	8.4
	20 + 20 + 35	2.29	2.29	4.01	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 20 + 50	1.91	1.91	4.78	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 20 + 60	1.72	1.72	5.16	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 20 + 71	1.55	1.55	5.50	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 25 + 25	2.46	3.07	3.07	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 25 + 35	2.15	2.69	3.76	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 25 + 50	1.81	2.26	4.53	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 25 + 60	1.64	2.05	4.91	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 25 + 71	1.48	1.85	5.26	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 35 + 35	1.91	3.34	3.34	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 35 + 50	1.64	2.87	4.10	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 35 + 60	1.50	2.62	4.49	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 35 + 71	1.37	2.39	4.85	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 50 + 50	1.43	3.58	3.58	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	25 + 25 + 25	2.87	2.87	2.87	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	25 + 25 + 35	2.53	2.53	3.54	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	25 + 25 + 50	2.15	2.15	4.30	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	25 + 25 + 60	1.95	1.95	4.69	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
25 + 25 + 71	1.78	1.78	5.05	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2	
25 + 35 + 35	2.26	3.17	3.17	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2	
25 + 35 + 50	1.95	2.74	3.91	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2	
25 + 35 + 60	1.79	2.51	4.30	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2	
25 + 50 + 50	1.72	3.44	3.44	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2	
35 + 35 + 35	2.87	2.87	2.87	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2	
35 + 35 + 50	2.51	2.51	3.58	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2	

Met 4 units op  
volgende pagina!

# Capaciteitstabel SCM 71 ZS-W

In combinatie met binnenunits  
anders dan SRK xxx ZSX-W

**STULZ**

CLIMATE. CUSTOMIZED.

Heating		Heating capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
4 units	20 + 20 + 20 + 20	2.15	2.15	2.15	2.15	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 20 + 20 + 25	2.02	2.02	2.02	2.53	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 20 + 20 + 35	1.81	1.81	1.81	3.17	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 20 + 20 + 50	1.56	1.56	1.56	3.91	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 20 + 20 + 60	1.43	1.43	1.43	4.30	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 20 + 25 + 25	1.91	1.91	2.39	2.39	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 20 + 25 + 35	1.72	1.72	2.15	3.01	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 20 + 25 + 50	1.50	1.50	1.87	3.74	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 20 + 25 + 60	1.38	1.38	1.72	4.13	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 20 + 35 + 35	1.56	1.56	2.74	2.74	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 20 + 35 + 50	1.38	1.38	2.41	3.44	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 25 + 25 + 25	1.81	2.26	2.26	2.26	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 25 + 25 + 35	1.64	2.05	2.05	2.87	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 25 + 25 + 50	1.43	1.79	1.79	3.58	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 25 + 35 + 35	1.50	1.87	2.62	2.62	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 35 + 35 + 35	1.38	2.41	2.41	2.41	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	25 + 25 + 25 + 25	2.15	2.15	2.15	2.15	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	25 + 25 + 25 + 35	1.95	1.95	1.95	2.74	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
25 + 25 + 25 + 50	1.72	1.72	1.72	3.44	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5	
25 + 25 + 35 + 35	1.79	1.79	2.51	2.51	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5	

# Capaciteitstabel SCM 71 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Uitsluitend in combinatie met SRK xxx ZSX-W

Indoor unit combination		Cooling capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
1 unit	20	2.0	-	-	-	1.8	2.0	3.4	480	500	950	2.4	2.3	2.2
	25	2.5	-	-	-	1.8	2.5	3.8	480	680	1080	3.2	3.1	3.0
	35	3.5	-	-	-	1.8	3.5	4.5	480	1010	1240	4.7	4.5	4.3
	50	5.0	-	-	-	1.8	5.0	6.2	480	1530	2100	7.0	6.7	6.4
	60	6.0	-	-	-	1.8	6.0	6.9	480	1880	2700	8.6	8.3	7.9
2 units	20 + 20	2.00	2.00	-	-	3.0	4.0	6.1	550	840	1910	4.0	3.8	3.6
	20 + 25	2.00	2.50	-	-	3.0	4.5	6.4	550	990	2060	4.6	4.4	4.3
	20 + 35	2.00	3.50	-	-	3.0	5.5	6.9	550	1320	2320	6.1	5.8	5.6
	20 + 50	2.03	5.07	-	-	3.0	7.1	7.7	550	1970	2750	9.0	8.7	8.3
	20 + 60	1.78	5.33	-	-	3.0	7.1	7.7	550	1970	2750	9.0	8.7	8.3
	25 + 25	2.50	2.50	-	-	3.0	5.0	6.8	550	1150	2270	5.4	5.1	4.9
	25 + 35	2.46	3.44	-	-	3.0	5.9	7.2	550	1470	2470	6.8	6.5	6.2
	25 + 50	2.37	4.73	-	-	3.0	7.1	7.7	550	1970	2750	9.0	8.7	8.3
	25 + 60	2.09	5.01	-	-	3.0	7.1	7.7	550	1970	2750	9.0	8.7	8.3
	35 + 35	3.55	3.55	-	-	3.0	7.1	7.7	550	1970	2750	9.0	8.7	8.3
	35 + 50	2.92	4.18	-	-	3.0	7.1	7.7	550	1970	2750	9.0	8.7	8.3
	35 + 60	2.62	4.48	-	-	3.0	7.1	7.7	550	1970	2750	9.0	8.7	8.3
	50 + 50	3.55	3.55	-	-	3.0	7.1	7.7	550	1970	2750	9.0	8.7	8.3
	50 + 60	3.23	3.87	-	-	3.0	7.1	7.7	550	1970	2750	9.0	8.7	8.3
	60 + 60	3.55	3.55	-	-	3.0	7.1	7.7	550	1970	2750	9.0	8.7	8.3

Met 3/4 units op  
volgende pagina's!

# Capaciteitstabel SCM 71 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Uitsluitend in combinatie met SRK xxx ZSX-W

Indoor unit combination		Cooling capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
3 units	20 + 20 + 20	2.00	2.00	2.00	-	3.7	6.0	8.2	670	1240	2750	5.8	5.5	5.3
	20 + 20 + 25	2.00	2.00	2.50	-	3.7	6.5	8.2	670	1390	2750	6.4	6.1	5.9
	20 + 20 + 35	1.89	1.89	3.31	-	3.7	7.1	8.2	670	1520	2750	7.0	6.7	6.4
	20 + 20 + 50	1.58	1.58	3.94	-	3.7	7.1	8.2	670	1520	2750	7.0	6.7	6.4
	20 + 20 + 60	1.42	1.42	4.26	-	3.7	7.1	8.2	670	1520	2750	7.0	6.7	6.4
	20 + 25 + 25	2.03	2.54	2.54	-	3.7	7.1	8.2	670	1520	2750	7.0	6.7	6.4
	20 + 25 + 35	1.78	2.22	3.11	-	3.7	7.1	8.2	670	1520	2750	7.0	6.7	6.4
	20 + 25 + 50	1.49	1.87	3.74	-	3.7	7.1	8.2	670	1520	2750	7.0	6.7	6.4
	20 + 25 + 60	1.35	1.69	4.06	-	3.7	7.1	8.2	670	1520	2750	7.0	6.7	6.4
	20 + 35 + 35	1.58	2.76	2.76	-	3.7	7.1	8.2	670	1520	2750	7.0	6.7	6.4
	20 + 35 + 50	1.35	2.37	3.38	-	3.7	7.1	8.2	670	1520	2750	7.0	6.7	6.4
	20 + 35 + 60	1.23	2.16	3.70	-	3.7	7.1	8.2	670	1520	2750	7.0	6.7	6.4
	20 + 50 + 50	1.18	2.96	2.96	-	3.7	7.1	8.2	670	1520	2750	7.0	6.7	6.4
	25 + 25 + 25	2.37	2.37	2.37	-	3.7	7.1	8.2	670	1520	2750	7.0	6.7	6.4
	25 + 25 + 35	2.09	2.09	2.92	-	3.7	7.1	8.2	670	1520	2750	7.0	6.7	6.4
	25 + 25 + 50	1.78	1.78	3.55	-	3.7	7.1	8.2	670	1520	2750	7.0	6.7	6.4
	25 + 25 + 60	1.61	1.61	3.87	-	3.7	7.1	8.2	670	1520	2750	7.0	6.7	6.4
	25 + 35 + 35	1.87	2.62	2.62	-	3.7	7.1	8.2	670	1520	2750	7.0	6.7	6.4
	25 + 35 + 50	1.61	2.26	3.23	-	3.7	7.1	8.2	670	1520	2750	7.0	6.7	6.4
	25 + 35 + 60	1.48	2.07	3.55	-	3.7	7.1	8.2	670	1520	2750	7.0	6.7	6.4
25 + 50 + 50	1.42	2.84	2.84	-	3.7	7.1	8.2	670	1520	2750	7.0	6.7	6.4	
35 + 35 + 35	2.37	2.37	2.37	-	3.7	7.1	8.2	670	1520	2750	7.0	6.7	6.4	
35 + 35 + 50	2.07	2.07	2.96	-	3.7	7.1	8.2	670	1520	2750	7.0	6.7	6.4	

Met 4 units op  
volgende pagina!

# Capaciteitstabel SCM 71 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Uitsluitend in combinatie met SRK xxx ZSX-W

Indoor unit combination		Cooling capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
4 units	20 + 20 + 20 + 20	1.78	1.78	1.78	1.78	4.4	7.1	8.8	890	1420	2750	6.5	6.2	6.0
	20 + 20 + 20 + 25	1.67	1.67	1.67	2.09	4.4	7.1	8.8	890	1420	2750	6.5	6.2	6.0
	20 + 20 + 20 + 35	1.49	1.49	1.49	2.62	4.4	7.1	8.8	890	1420	2750	6.5	6.2	6.0
	20 + 20 + 20 + 50	1.29	1.29	1.29	3.23	4.4	7.1	8.8	890	1420	2750	6.5	6.2	6.0
	20 + 20 + 20 + 60	1.18	1.18	1.18	3.55	4.4	7.1	8.8	890	1420	2750	6.5	6.2	6.0
	20 + 20 + 25 + 25	1.58	1.58	1.97	1.97	4.4	7.1	8.8	890	1420	2750	6.5	6.2	6.0
	20 + 20 + 25 + 35	1.42	1.42	1.78	2.49	4.4	7.1	8.8	890	1420	2750	6.5	6.2	6.0
	20 + 20 + 25 + 50	1.23	1.23	1.54	3.09	4.4	7.1	8.8	890	1420	2750	6.5	6.2	6.0
	20 + 20 + 25 + 60	1.14	1.14	1.42	3.41	4.4	7.1	8.8	890	1420	2750	6.5	6.2	6.0
	20 + 20 + 35 + 35	1.29	1.29	2.26	2.26	4.4	7.1	8.8	890	1420	2750	6.5	6.2	6.0
	20 + 20 + 35 + 50	1.14	1.14	1.99	2.84	4.4	7.1	8.8	890	1420	2750	6.5	6.2	6.0
	20 + 25 + 25 + 25	1.49	1.87	1.87	1.87	4.4	7.1	8.8	890	1420	2750	6.5	6.2	6.0
	20 + 25 + 25 + 35	1.35	1.69	1.69	2.37	4.4	7.1	8.8	890	1420	2750	6.5	6.2	6.0
	20 + 25 + 25 + 50	1.18	1.48	1.48	2.96	4.4	7.1	8.8	890	1420	2750	6.5	6.2	6.0
	20 + 25 + 35 + 35	1.23	1.54	2.16	2.16	4.4	7.1	8.8	890	1420	2750	6.5	6.2	6.0
	20 + 35 + 35 + 35	1.14	1.99	1.99	1.99	4.4	7.1	8.8	890	1420	2750	6.5	6.2	6.0
	25 + 25 + 25 + 25	1.78	1.78	1.78	1.78	4.4	7.1	8.8	890	1420	2750	6.5	6.2	6.0
	25 + 25 + 25 + 35	1.61	1.61	1.61	2.26	4.4	7.1	8.8	890	1420	2750	6.5	6.2	6.0
25 + 25 + 25 + 50	1.42	1.42	1.42	2.84	4.4	7.1	8.8	890	1420	2750	6.5	6.2	6.0	
25 + 25 + 35 + 35	1.48	1.48	2.07	2.07	4.4	7.1	8.8	890	1420	2750	6.5	6.2	6.0	

# Capaciteitstabel SCM 71 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Uitsluitend in combinatie met SRK xxx ZSX-W

Indoor unit combination		Heating capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
1 unit	20	3.0	-	-	-	1.1	3.0	3.7	390	840	1330	4.0	3.8	3.6
	25	3.4	-	-	-	1.1	3.4	4.2	390	1000	1510	4.7	4.5	4.3
	35	4.5	-	-	-	1.1	4.5	5.0	390	1330	1790	6.2	5.9	5.7
	50	5.8	-	-	-	1.1	5.8	6.5	390	1780	2310	8.3	7.9	7.6
	60	6.8	-	-	-	1.1	6.8	7.5	390	2100	2660	9.7	9.3	8.9
2 units	20 + 20	2.70	2.70	-	-	1.5	5.4	7.4	350	1280	1870	6.0	5.7	5.5
	20 + 25	2.62	3.28	-	-	1.5	5.9	7.7	350	1410	2130	6.6	6.3	6.0
	20 + 35	2.51	4.39	-	-	1.5	6.9	8.3	350	1680	2650	7.8	7.5	7.1
	20 + 50	2.46	6.14	-	-	1.5	8.6	8.9	350	2100	3000	9.7	9.3	8.9
	20 + 60	2.15	6.45	-	-	1.5	8.6	8.9	350	2100	3000	9.7	9.3	8.9
	25 + 25	3.20	3.20	-	-	1.5	6.4	8.1	350	1540	2480	7.1	6.8	6.5
	25 + 35	3.08	4.32	-	-	1.5	7.4	8.6	350	1810	2910	8.4	8.0	7.7
	25 + 50	2.87	5.73	-	-	1.5	8.6	8.9	350	2100	3000	9.7	9.3	8.9
	25 + 60	2.53	6.07	-	-	1.5	8.6	8.9	350	2100	3000	9.7	9.3	8.9
	35 + 35	4.30	4.30	-	-	1.5	8.6	8.9	350	2100	3000	9.7	9.3	8.9
	35 + 50	3.54	5.06	-	-	1.5	8.6	8.9	350	2100	3000	9.7	9.3	8.9
	35 + 60	3.17	5.43	-	-	1.5	8.6	8.9	350	2100	3000	9.7	9.3	8.9
	50 + 50	4.30	4.30	-	-	1.5	8.6	8.9	350	2100	3000	9.7	9.3	8.9
	50 + 60	3.91	4.69	-	-	1.5	8.6	8.9	350	2100	3000	9.7	9.3	8.9
60 + 60	4.30	4.30	-	-	1.5	8.6	8.9	350	2100	3000	9.7	9.3	8.9	

Met 3/4 units op  
volgende pagina's!

# Capaciteitstabel SCM 71 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Uitsluitend in combinatie met SRK xxx ZSX-W

Indoor unit combination		Heating capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
3 units	20 + 20 + 20	2.57	2.57	2.57	-	1.6	7.7	9.1	370	1830	3000	8.5	8.1	7.8
	20 + 20 + 25	2.46	2.46	3.08	-	1.6	8.0	9.1	370	1930	3000	9.0	8.6	8.2
	20 + 20 + 35	2.29	2.29	4.01	-	1.6	8.6	9.1	370	2060	3000	9.6	9.1	8.8
	20 + 20 + 50	1.91	1.91	4.78	-	1.6	8.6	9.1	370	2060	3000	9.6	9.1	8.8
	20 + 20 + 60	1.72	1.72	5.16	-	1.6	8.6	9.1	370	2060	3000	9.6	9.1	8.8
	20 + 25 + 25	2.46	3.07	3.07	-	1.6	8.6	9.1	370	2060	3000	9.6	9.1	8.8
	20 + 25 + 35	2.15	2.69	3.76	-	1.6	8.6	9.1	370	2060	3000	9.6	9.1	8.8
	20 + 25 + 50	1.81	2.26	4.53	-	1.6	8.6	9.1	370	2060	3000	9.6	9.1	8.8
	20 + 25 + 60	1.64	2.05	4.91	-	1.6	8.6	9.1	370	2060	3000	9.6	9.1	8.8
	20 + 35 + 35	1.91	3.34	3.34	-	1.6	8.6	9.1	370	2060	3000	9.6	9.1	8.8
	20 + 35 + 50	1.64	2.87	4.10	-	1.6	8.6	9.1	370	2060	3000	9.6	9.1	8.8
	20 + 35 + 60	1.50	2.62	4.49	-	1.6	8.6	9.1	370	2060	3000	9.6	9.1	8.8
	20 + 50 + 50	1.43	3.58	3.58	-	1.6	8.6	9.1	370	2060	3000	9.6	9.1	8.8
	25 + 25 + 25	2.87	2.87	2.87	-	1.6	8.6	9.1	370	2060	3000	9.6	9.1	8.8
	25 + 25 + 35	2.53	2.53	3.54	-	1.6	8.6	9.1	370	2060	3000	9.6	9.1	8.8
	25 + 25 + 50	2.15	2.15	4.30	-	1.6	8.6	9.1	370	2060	3000	9.6	9.1	8.8
	25 + 25 + 60	1.95	1.95	4.69	-	1.6	8.6	9.1	370	2060	3000	9.6	9.1	8.8
	25 + 35 + 35	2.26	3.17	3.17	-	1.6	8.6	9.1	370	2060	3000	9.6	9.1	8.8
25 + 35 + 50	1.95	2.74	3.91	-	1.6	8.6	9.1	370	2060	3000	9.6	9.1	8.8	
25 + 35 + 60	1.79	2.51	4.30	-	1.6	8.6	9.1	370	2060	3000	9.6	9.1	8.8	
25 + 50 + 50	1.72	3.44	3.44	-	1.6	8.6	9.1	370	2060	3000	9.6	9.1	8.8	
35 + 35 + 35	2.87	2.87	2.87	-	1.6	8.6	9.1	370	2060	3000	9.6	9.1	8.8	
35 + 35 + 50	2.51	2.51	3.58	-	1.6	8.6	9.1	370	2060	3000	9.6	9.1	8.8	

Met 4 units op  
volgende pagina!

# Capaciteitstabel SCM 71 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Uitsluitend in combinatie met SRK xxx ZSX-W

Heating		Heating capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
4 units	20 + 20 + 20 + 20	2.15	2.15	2.15	2.15	1.7	8.6	9.4	350	1750	3000	8.1	7.8	7.4
	20 + 20 + 20 + 25	2.02	2.02	2.02	2.53	1.7	8.6	9.4	350	1750	3000	8.1	7.8	7.4
	20 + 20 + 20 + 35	1.81	1.81	1.81	3.17	1.7	8.6	9.4	350	1750	3000	8.1	7.8	7.4
	20 + 20 + 20 + 50	1.56	1.56	1.56	3.91	1.7	8.6	9.4	350	1750	3000	8.1	7.8	7.4
	20 + 20 + 20 + 60	1.43	1.43	1.43	4.30	1.7	8.6	9.4	350	1750	3000	8.1	7.8	7.4
	20 + 20 + 25 + 25	1.91	1.91	2.39	2.39	1.7	8.6	9.4	350	1750	3000	8.1	7.8	7.4
	20 + 20 + 25 + 35	1.72	1.72	2.15	3.01	1.7	8.6	9.4	350	1750	3000	8.1	7.8	7.4
	20 + 20 + 25 + 50	1.50	1.50	1.87	3.74	1.7	8.6	9.4	350	1750	3000	8.1	7.8	7.4
	20 + 20 + 25 + 60	1.38	1.38	1.72	4.13	1.7	8.6	9.4	350	1750	3000	8.1	7.8	7.4
	20 + 20 + 35 + 35	1.56	1.56	2.74	2.74	1.7	8.6	9.4	350	1750	3000	8.1	7.8	7.4
	20 + 20 + 35 + 50	1.38	1.38	2.41	3.44	1.7	8.6	9.4	350	1750	3000	8.1	7.8	7.4
	20 + 25 + 25 + 25	1.81	2.26	2.26	2.26	1.7	8.6	9.4	350	1750	3000	8.1	7.8	7.4
	20 + 25 + 25 + 35	1.64	2.05	2.05	2.87	1.7	8.6	9.4	350	1750	3000	8.1	7.8	7.4
	20 + 25 + 25 + 50	1.43	1.79	1.79	3.58	1.7	8.6	9.4	350	1750	3000	8.1	7.8	7.4
	20 + 25 + 35 + 35	1.50	1.87	2.62	2.62	1.7	8.6	9.4	350	1750	3000	8.1	7.8	7.4
	20 + 35 + 35 + 35	1.38	2.41	2.41	2.41	1.7	8.6	9.4	350	1750	3000	8.1	7.8	7.4
	25 + 25 + 25 + 25	2.15	2.15	2.15	2.15	1.7	8.6	9.4	350	1750	3000	8.1	7.8	7.4
25 + 25 + 25 + 35	1.95	1.95	1.95	2.74	1.7	8.6	9.4	350	1750	3000	8.1	7.8	7.4	
25 + 25 + 25 + 50	1.72	1.72	1.72	3.44	1.7	8.6	9.4	350	1750	3000	8.1	7.8	7.4	
25 + 25 + 35 + 35	1.79	1.79	2.51	2.51	1.7	8.6	9.4	350	1750	3000	8.1	7.8	7.4	



# Combinatietabel

## SCM 71 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Aansluitbare binnendelen

Aantal binnenunits minimaal: 2

Aantal binnenunits maximaal: 4

Maximaal aansluitbare capaciteit: 12,5kW

Uitzonderingen: Geen

	Aansluitbaar
SRK 20 ZS-W	Ja
SRK 25 ZS-W	Ja
SRK 35 ZS-W	Ja
SRK 50 ZS-W	Ja
SRK 20 ZSX-W	Ja
SRK 25 ZSX-W	Ja
SRK 35 ZSX-W	Ja
SRK 50 ZSX-W	Ja
SRK 60 ZSX-W	Ja
SRK 71 ZR-W	Ja
FDTC 25 VH	Ja
FDTC 35 VH	Ja
FDTC 50 VH	Ja
FDTC 60 VH	Ja
FDTC 25 VF	Nee
FDTC 35 VF	Nee
FDTC 50 VF	Nee
FDTC 60 VF	Nee

	Aansluitbaar
SRR 25 ZM-W	Ja
SRR 35 ZM-W	Ja
SRR 50 ZS-W	Ja
SRR 60 ZS-W	Ja
SRR 25 ZM-S	Nee
SRR 35 ZM-S	Nee
SRR 50 ZM-S	Nee
SRR 60 ZM-S	Nee
FDUM 50 VH	Ja
FDE 50 VH	Ja
SRF 25 ZMX-S	Nee
SRF 35 ZMX-S	Nee
SRF 50 ZMX-S	Nee

# Capaciteitstabel

## SCM 80 ZS-W

In combinatie met binnenunits  
anders dan SRK xxx ZSX-W

**STULZ**

CLIMATE. CUSTOMIZED.

Indoor unit combination		Cooling capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
1 unit	20	2.0	-	-	-	1.8	2.0	2.7	480	530	950	2.5	2.4	2.3
	25	2.5	-	-	-	1.8	2.5	3.2	480	730	1080	3.5	3.3	3.2
	35	3.5	-	-	-	1.8	3.5	3.7	480	1120	1240	5.2	5.0	4.8
	50	5.0	-	-	-	1.8	5.0	5.8	480	1710	2100	7.9	7.5	7.2
	60	6.0	-	-	-	1.8	6.0	6.7	480	2140	2700	9.8	9.4	9.0
	71	7.1	-	-	-	1.8	7.1	7.2	480	2430	2830	11.2	10.7	10.2
2 units	20 + 20	2.00	2.00	-	-	3.0	4.0	5.8	550	930	1910	4.4	4.2	4.0
	20 + 25	2.00	2.50	-	-	3.0	4.5	6.1	550	1170	2060	5.5	5.2	5.0
	20 + 35	2.00	3.50	-	-	3.0	5.5	6.6	550	1590	2320	7.3	7.0	6.7
	20 + 50	2.03	5.07	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	20 + 60	1.78	5.33	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	20 + 71	1.56	5.54	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	25 + 25	2.50	2.50	-	-	3.0	5.0	6.5	550	1360	2270	6.3	6.0	5.8
	25 + 35	2.46	3.44	-	-	3.0	5.9	6.8	550	1780	2470	8.2	7.8	7.5
	25 + 50	2.37	4.73	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	25 + 60	2.09	5.01	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	25 + 71	1.85	5.25	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	35 + 35	3.55	3.55	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	35 + 50	2.92	4.18	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	35 + 60	2.62	4.48	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	35 + 71	2.34	4.76	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	50 + 50	3.55	3.55	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	50 + 60	3.23	3.87	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
	50 + 71	2.93	4.17	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8
60 + 60	3.55	3.55	-	-	3.0	7.1	7.3	550	2340	2750	10.7	10.3	9.8	

Met 3/4 units op  
volgende pagina's!

# Capaciteitstabel SCM 80 ZS-W

In combinatie met binnenunits  
anders dan SRK xxx ZSX-W

**STULZ**

CLIMATE. CUSTOMIZED.

Indoor unit combination		Cooling capacity (kW)						Power consumption (W)			Standard current (A)			
		Indoor unit capacity (kW)				Total capacity (kW)		Min.	Standard	Max.	220V	230V	240V	
		A	B	C	D	Min.	Standard							Max.
3 units	20 + 20 + 20	2.00	2.00	2.00	-	3.7	6.0	7.8	670	1440	2750	6.6	6.4	6.1
	20 + 20 + 25	2.00	2.00	2.50	-	3.7	6.5	7.8	670	1630	2750	7.5	7.2	6.9
	20 + 20 + 35	1.89	1.89	3.31	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 20 + 50	1.58	1.58	3.94	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 20 + 60	1.42	1.42	4.26	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 20 + 71	1.28	1.28	4.54	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 25 + 25	2.03	2.54	2.54	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 25 + 35	1.78	2.22	3.11	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 25 + 50	1.49	1.87	3.74	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 25 + 60	1.35	1.69	4.06	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 25 + 71	1.22	1.53	4.35	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 35 + 35	1.58	2.76	2.76	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 35 + 50	1.35	2.37	3.38	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 35 + 60	1.23	2.16	3.70	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 35 + 71	1.13	1.97	4.00	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	20 + 50 + 50	1.18	2.96	2.96	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	25 + 25 + 25	2.37	2.37	2.37	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	25 + 25 + 35	2.09	2.09	2.92	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	25 + 25 + 50	1.78	1.78	3.55	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	25 + 25 + 60	1.61	1.61	3.87	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	25 + 25 + 71	1.47	1.47	4.17	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	25 + 35 + 35	1.87	2.62	2.62	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	25 + 35 + 50	1.61	2.26	3.23	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	25 + 35 + 60	1.48	2.07	3.55	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	25 + 50 + 50	1.42	2.84	2.84	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	35 + 35 + 35	2.37	2.37	2.37	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9
	35 + 35 + 50	2.07	2.07	2.96	-	3.7	7.1	7.8	670	1870	2750	8.6	8.2	7.9

Met 4 units op  
volgende pagina!

# Capaciteitstabel

## SCM 80 ZS-W

In combinatie met binnenunits  
anders dan SRK xxx ZSX-W

**STULZ**

CLIMATE. CUSTOMIZED.

Indoor unit combination		Cooling capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
4 units	20 + 20 + 20 + 20	1.78	1.78	1.78	1.78	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 20 + 20 + 25	1.67	1.67	1.67	2.09	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 20 + 20 + 35	1.49	1.49	1.49	2.62	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 20 + 20 + 50	1.29	1.29	1.29	3.23	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 20 + 20 + 60	1.18	1.18	1.18	3.55	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 20 + 25 + 25	1.58	1.58	1.97	1.97	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 20 + 25 + 35	1.42	1.42	1.78	2.49	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 20 + 25 + 50	1.23	1.23	1.54	3.09	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 20 + 25 + 60	1.14	1.14	1.42	3.41	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 20 + 35 + 35	1.29	1.29	2.26	2.26	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 20 + 35 + 50	1.14	1.14	1.99	2.84	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 25 + 25 + 25	1.49	1.87	1.87	1.87	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 25 + 25 + 35	1.35	1.69	1.69	2.37	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 25 + 25 + 50	1.18	1.48	1.48	2.96	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 25 + 35 + 35	1.23	1.54	2.16	2.16	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	20 + 35 + 35 + 35	1.14	1.99	1.99	1.99	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	25 + 25 + 25 + 25	1.78	1.78	1.78	1.78	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
	25 + 25 + 25 + 35	1.61	1.61	1.61	2.26	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5
25 + 25 + 25 + 50	1.42	1.42	1.42	2.84	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5	
25 + 25 + 35 + 35	1.48	1.48	2.07	2.07	4.4	7.1	8.3	890	1780	2750	8.2	7.8	7.5	

# Capaciteitstabel SCM 80 ZS-W

In combinatie met binnenunits  
anders dan SRK xxx ZSX-W

**STULZ**

CLIMATE. CUSTOMIZED.

Indoor unit combination		Heating capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
1 unit	20	3.0	-	-	-	1.1	3.0	3.5	390	1060	1330	5.0	4.8	4.6
	25	3.4	-	-	-	1.1	3.4	4.0	390	1220	1510	5.7	5.5	5.2
	35	4.5	-	-	-	1.1	4.5	4.8	390	1510	1790	7.0	6.7	6.4
	50	5.8	-	-	-	1.1	5.8	6.2	390	1950	2310	9.0	8.7	8.3
	60	6.8	-	-	-	1.1	6.8	7.1	390	2240	2660	10.4	9.9	9.5
	71	8.0	-	-	-	1.1	8.0	8.1	390	2740	3000	12.7	12.2	11.6
2 units	20 + 20	2.70	2.70	-	-	1.5	5.4	7.0	350	1370	1870	6.4	6.1	5.9
	20 + 25	2.62	3.28	-	-	1.5	5.9	7.3	350	1560	2130	7.3	6.9	6.7
	20 + 35	2.51	4.39	-	-	1.5	6.9	7.9	350	1950	2650	9.0	8.7	8.3
	20 + 50	2.46	6.14	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	20 + 60	2.15	6.45	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	20 + 71	1.89	6.71	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	25 + 25	3.20	3.20	-	-	1.5	6.4	7.7	350	1740	2480	8.1	7.7	7.4
	25 + 35	3.08	4.32	-	-	1.5	7.4	8.2	350	2130	2910	9.9	9.4	9.1
	25 + 50	2.87	5.73	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	25 + 60	2.53	6.07	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	25 + 71	2.24	6.36	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	35 + 35	4.30	4.30	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	35 + 50	3.54	5.06	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	35 + 60	3.17	5.43	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	35 + 71	2.84	5.76	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	50 + 50	4.30	4.30	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	50 + 60	3.91	4.69	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
	50 + 71	3.55	5.05	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5
60 + 60	4.30	4.30	-	-	1.5	8.6	8.7	350	2460	3000	11.4	10.9	10.5	

Met 3/4 units op  
volgende pagina's

# Capaciteitstabel SCM 80 ZS-W

In combinatie met binnenunits  
anders dan SRK xxx ZSX-W

**STULZ**

CLIMATE. CUSTOMIZED.

Indoor unit combination		Heating capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
3 units	20 + 20 + 20	2.57	2.57	2.57	-	1.6	7.7	8.9	370	1870	3000	8.7	8.3	8.0
	20 + 20 + 25	2.46	2.46	3.08	-	1.6	8.0	8.9	370	1970	3000	9.1	8.7	8.4
	20 + 20 + 35	2.29	2.29	4.01	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 20 + 50	1.91	1.91	4.78	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 20 + 60	1.72	1.72	5.16	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 20 + 71	1.55	1.55	5.50	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 25 + 25	2.46	3.07	3.07	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 25 + 35	2.15	2.69	3.76	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 25 + 50	1.81	2.26	4.53	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 25 + 60	1.64	2.05	4.91	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 25 + 71	1.48	1.85	5.26	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 35 + 35	1.91	3.34	3.34	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 35 + 50	1.64	2.87	4.10	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 35 + 60	1.50	2.62	4.49	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 35 + 71	1.37	2.39	4.85	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	20 + 50 + 50	1.43	3.58	3.58	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	25 + 25 + 25	2.87	2.87	2.87	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	25 + 25 + 35	2.53	2.53	3.54	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	25 + 25 + 50	2.15	2.15	4.30	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	25 + 25 + 60	1.95	1.95	4.69	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	25 + 25 + 71	1.78	1.78	5.05	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	25 + 35 + 35	2.26	3.17	3.17	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	25 + 35 + 50	1.95	2.74	3.91	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	25 + 35 + 60	1.79	2.51	4.30	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	25 + 50 + 50	1.72	3.44	3.44	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	35 + 35 + 35	2.87	2.87	2.87	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2
	35 + 35 + 50	2.51	2.51	3.58	-	1.6	8.6	8.9	370	2410	3000	11.2	10.7	10.2

Met 4 units op  
volgende pagina!

# Capaciteitstabel SCM 80 ZS-W

In combinatie met binnenunits  
anders dan SRK xxx ZSX-W

**STULZ**

CLIMATE. CUSTOMIZED.

Heating		Heating capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
4 units	20 + 20 + 20 + 20	2.15	2.15	2.15	2.15	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 20 + 20 + 25	2.02	2.02	2.02	2.53	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 20 + 20 + 35	1.81	1.81	1.81	3.17	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 20 + 20 + 50	1.56	1.56	1.56	3.91	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 20 + 20 + 60	1.43	1.43	1.43	4.30	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 20 + 25 + 25	1.91	1.91	2.39	2.39	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 20 + 25 + 35	1.72	1.72	2.15	3.01	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 20 + 25 + 50	1.50	1.50	1.87	3.74	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 20 + 25 + 60	1.38	1.38	1.72	4.13	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 20 + 35 + 35	1.56	1.56	2.74	2.74	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 20 + 35 + 50	1.38	1.38	2.41	3.44	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 25 + 25 + 25	1.81	2.26	2.26	2.26	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 25 + 25 + 35	1.64	2.05	2.05	2.87	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 25 + 25 + 50	1.43	1.79	1.79	3.58	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 25 + 35 + 35	1.50	1.87	2.62	2.62	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	20 + 35 + 35 + 35	1.38	2.41	2.41	2.41	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	25 + 25 + 25 + 25	2.15	2.15	2.15	2.15	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
	25 + 25 + 25 + 35	1.95	1.95	1.95	2.74	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5
25 + 25 + 25 + 50	1.72	1.72	1.72	3.44	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5	
25 + 25 + 35 + 35	1.79	1.79	2.51	2.51	1.7	8.6	9.1	350	1990	3000	9.2	8.8	8.5	

# Capaciteitstabel SCM 80 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Uitsluitend in combinatie met SRK xxx ZSX-W

Indoor unit combination		Cooling capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
1 unit	20	2.0	-	-	-	1.8	2.0	2.8	480	500	950	2.4	2.3	2.2
	25	2.5	-	-	-	1.8	2.5	3.4	480	680	1080	3.2	3.1	3.0
	35	3.5	-	-	-	1.8	3.5	3.9	480	1010	1240	4.7	4.5	4.3
	50	5.0	-	-	-	1.8	5.0	6.1	480	1530	2100	7.0	6.7	6.4
	60	6.0	-	-	-	1.8	6.0	7.0	480	1880	2700	8.6	8.3	7.9
2 units	20 + 20	2.00	2.00	-	-	3.0	4.0	6.1	550	840	1910	4.0	3.8	3.6
	20 + 25	2.00	2.50	-	-	3.0	4.5	6.4	550	990	2060	4.6	4.4	4.3
	20 + 35	2.00	3.50	-	-	3.0	5.5	6.9	550	1320	2320	6.1	5.8	5.6
	20 + 50	2.03	5.07	-	-	3.0	7.1	8.5	550	1970	2830	9.0	8.7	8.3
	20 + 60	2.00	6.00	-	-	3.0	8.0	8.5	550	2420	2830	11.1	10.6	10.2
	25 + 25	2.50	2.50	-	-	3.0	5.0	6.8	550	1150	2270	5.4	5.1	4.9
	25 + 35	2.46	3.44	-	-	3.0	5.9	7.2	550	1560	2470	7.2	6.9	6.6
	25 + 50	2.47	4.93	-	-	3.0	7.4	8.5	550	2090	2830	9.6	9.2	8.8
	25 + 60	2.35	5.65	-	-	3.0	8.0	8.5	550	2420	2830	11.1	10.6	10.2
	35 + 35	3.55	3.55	-	-	3.0	7.1	8.5	550	1970	2830	9.0	8.7	8.3
	35 + 50	3.29	4.71	-	-	3.0	8.0	8.5	550	2420	2830	11.1	10.6	10.2
	35 + 60	2.95	5.05	-	-	3.0	8.0	8.5	550	2420	2830	11.1	10.6	10.2
	50 + 50	4.00	4.00	-	-	3.0	8.0	8.5	550	2420	2830	11.1	10.6	10.2
	50 + 60	3.64	4.36	-	-	3.0	8.0	8.5	550	2420	2830	11.1	10.6	10.2
60 + 60	4.00	4.00	-	-	3.0	8.0	8.5	550	2420	2830	11.1	10.6	10.2	

Met 3/4 units op volgende pagina's!



# Capaciteitstabel SCM 80 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Uitsluitend in combinatie met SRK xxx ZSX-W

Indoor unit combination		Cooling capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
3 units	20 + 20 + 20	2.00	2.00	2.00	-	3.7	6.0	8.8	670	1240	2830	5.8	5.5	5.3
	20 + 20 + 25	2.00	2.00	2.50	-	3.7	6.5	8.8	670	1390	2830	6.4	6.1	5.9
	20 + 20 + 35	1.89	1.89	3.31	-	3.7	7.1	8.8	670	1520	2830	7.0	6.7	6.4
	20 + 20 + 50	1.78	1.78	4.44	-	3.7	8.0	8.8	670	1910	2830	8.8	8.4	8.0
	20 + 20 + 60	1.60	1.60	4.80	-	3.7	8.0	8.8	670	1910	2830	8.8	8.4	8.0
	20 + 25 + 25	2.03	2.54	2.54	-	3.7	7.1	8.8	670	1520	2830	7.0	6.7	6.4
	20 + 25 + 35	2.00	2.50	3.50	-	3.7	8.0	8.8	670	1910	2830	8.8	8.4	8.0
	20 + 25 + 50	1.68	2.11	4.21	-	3.7	8.0	8.8	670	1910	2830	8.8	8.4	8.0
	20 + 25 + 60	1.52	1.90	4.57	-	3.7	8.0	8.8	670	1910	2830	8.8	8.4	8.0
	20 + 35 + 35	1.78	3.11	3.11	-	3.7	8.0	8.8	670	1910	2830	8.8	8.4	8.0
	20 + 35 + 50	1.52	2.67	3.81	-	3.7	8.0	8.8	670	1910	2830	8.8	8.4	8.0
	20 + 35 + 60	1.39	2.43	4.17	-	3.7	8.0	8.8	670	1910	2830	8.8	8.4	8.0
	20 + 50 + 50	1.33	3.33	3.33	-	3.7	8.0	8.8	670	1910	2830	8.8	8.4	8.0
	20 + 50 + 60	1.23	3.08	3.69	-	3.7	8.0	8.8	670	1910	2830	8.8	8.4	8.0
	25 + 25 + 25	2.37	2.37	2.37	-	3.7	7.1	8.8	670	1520	2830	7.0	6.7	6.4
	25 + 25 + 35	2.35	2.35	3.29	-	3.7	8.0	8.8	670	1910	2830	8.8	8.4	8.0
	25 + 25 + 50	2.00	2.00	4.00	-	3.7	8.0	8.8	670	1910	2830	8.8	8.4	8.0
	25 + 25 + 60	1.82	1.82	4.36	-	3.7	8.0	8.8	670	1910	2830	8.8	8.4	8.0
	25 + 35 + 35	2.11	2.95	2.95	-	3.7	8.0	8.8	670	1910	2830	8.8	8.4	8.0
	25 + 35 + 50	1.82	2.55	3.64	-	3.7	8.0	8.8	670	1910	2830	8.8	8.4	8.0
	25 + 35 + 60	1.67	2.33	4.00	-	3.7	8.0	8.8	670	1910	2830	8.8	8.4	8.0
	25 + 50 + 50	1.60	3.20	3.20	-	3.7	8.0	8.8	670	1910	2830	8.8	8.4	8.0
	25 + 50 + 60	1.48	2.96	3.56	-	3.7	8.0	8.8	670	1910	2830	8.8	8.4	8.0
	35 + 35 + 35	2.67	2.67	2.67	-	3.7	8.0	8.8	670	1910	2830	8.8	8.4	8.0
	35 + 35 + 50	2.33	2.33	3.33	-	3.7	8.0	8.8	670	1910	2830	8.8	8.4	8.0
	35 + 35 + 60	2.15	2.15	3.69	-	3.7	8.0	8.8	670	1910	2830	8.8	8.4	8.0
	35 + 50 + 50	2.07	2.96	2.96	-	3.7	8.0	8.8	670	1910	2830	8.8	8.4	8.0

Met 4 units op  
volgende pagina!

# Capaciteitstabel

## SCM 80 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Uitsluitend in combinatie met SRK xxx ZSX-W

Indoor unit combination		Cooling capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
4 units	20 + 20 + 20 + 20	2.00	2.00	2.00	2.00	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	20 + 20 + 20 + 25	1.88	1.88	1.88	2.35	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	20 + 20 + 20 + 35	1.68	1.68	1.68	2.95	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	20 + 20 + 20 + 50	1.45	1.45	1.45	3.64	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	20 + 20 + 20 + 60	1.33	1.33	1.33	4.00	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	20 + 20 + 25 + 25	1.78	1.78	2.22	2.22	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	20 + 20 + 25 + 35	1.60	1.60	2.00	2.80	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	20 + 20 + 25 + 50	1.39	1.39	1.74	3.48	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	20 + 20 + 25 + 60	1.28	1.28	1.60	3.84	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	20 + 20 + 35 + 35	1.45	1.45	2.55	2.55	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	20 + 20 + 35 + 50	1.28	1.28	2.24	3.20	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	20 + 20 + 35 + 60	1.19	1.19	2.07	3.56	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	20 + 25 + 25 + 25	1.68	2.11	2.11	2.11	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	20 + 25 + 25 + 35	1.52	1.90	1.90	2.67	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	20 + 25 + 25 + 50	1.33	1.67	1.67	3.33	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	20 + 25 + 25 + 60	1.23	1.54	1.54	3.69	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	20 + 25 + 35 + 35	1.39	1.74	2.43	2.43	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	20 + 25 + 35 + 50	1.23	1.54	2.15	3.08	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	20 + 35 + 35 + 35	1.28	2.24	2.24	2.24	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	25 + 25 + 25 + 25	2.00	2.00	2.00	2.00	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	25 + 25 + 25 + 35	1.82	1.82	1.82	2.55	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	25 + 25 + 25 + 50	1.60	1.60	1.60	3.20	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	25 + 25 + 25 + 60	1.48	1.48	1.48	3.56	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	25 + 25 + 35 + 35	1.67	1.67	2.33	2.33	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	25 + 25 + 35 + 50	1.48	1.48	2.07	2.96	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2
	25 + 35 + 35 + 35	1.54	2.15	2.15	2.15	4.4	8.0	9.2	890	1700	2830	7.8	7.5	7.2

# Capaciteitstabel SCM 80 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Uitsluitend in combinatie met SRK xxx ZSX-W

Indoor unit combination		Heating capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
1 unit	20	3.0	-	-	-	1.1	3.0	3.7	390	840	1330	4.0	3.8	3.6
	25	3.4	-	-	-	1.1	3.4	4.2	390	1000	1510	4.7	4.5	4.3
	35	4.5	-	-	-	1.1	4.5	5.0	390	1330	1790	6.2	5.9	5.7
	50	5.8	-	-	-	1.1	5.8	6.5	390	1780	2310	8.3	7.9	7.6
	60	6.8	-	-	-	1.1	6.8	7.5	390	2100	2660	9.7	9.3	8.9
2 units	20 + 20	2.70	2.70	-	-	1.5	5.4	7.4	350	1280	1870	6.0	5.7	5.5
	20 + 25	2.62	3.28	-	-	1.5	5.9	7.7	350	1410	2130	6.6	6.3	6.0
	20 + 35	2.51	4.39	-	-	1.5	6.9	8.3	350	1680	2650	7.8	7.5	7.1
	20 + 50	2.46	6.14	-	-	1.5	8.6	9.5	350	2100	3120	9.7	9.3	8.9
	20 + 60	2.33	6.98	-	-	1.5	9.3	9.5	350	2300	3120	10.7	10.2	9.8
	25 + 25	3.20	3.20	-	-	1.5	6.4	8.1	350	1540	2480	7.1	6.8	6.5
	25 + 35	3.08	4.32	-	-	1.5	7.4	8.6	350	1810	2910	8.4	8.0	7.7
	25 + 50	2.87	5.73	-	-	1.5	8.6	9.5	350	2100	3120	9.7	9.3	8.9
	25 + 60	2.74	6.56	-	-	1.5	9.3	9.5	350	2300	3120	10.7	10.2	9.8
	35 + 35	4.30	4.30	-	-	1.5	8.6	9.5	350	2100	3120	9.7	9.3	8.9
	35 + 50	3.83	5.47	-	-	1.5	9.3	9.5	350	2300	3120	10.7	10.2	9.8
	35 + 60	3.43	5.87	-	-	1.5	9.3	9.5	350	2300	3120	10.7	10.2	9.8
	50 + 50	4.65	4.65	-	-	1.5	9.3	9.5	350	2300	3120	10.7	10.2	9.8
	50 + 60	4.23	5.07	-	-	1.5	9.3	9.5	350	2300	3120	10.7	10.2	9.8
60 + 60	4.65	4.65	-	-	1.5	9.3	9.5	350	2300	3120	10.7	10.2	9.8	

Met 3/4 units op volgende pagina's!

# Capaciteitstabel SCM 80 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Uitsluitend in combinatie met SRK xxx ZSX-W

Indoor unit combination		Heating capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	Max.						
3 units	20 + 20 + 20	2.57	2.57	2.57	-	1.6	7.7	9.6	370	1830	3120	8.5	8.1	7.8
	20 + 20 + 25	2.46	2.46	3.08	-	1.6	8.0	9.6	370	1930	3120	9.0	8.6	8.2
	20 + 20 + 35	2.29	2.29	4.01	-	1.6	8.6	9.6	370	2060	3120	9.6	9.1	8.8
	20 + 20 + 50	2.07	2.07	5.17	-	1.6	9.3	9.6	370	2250	3120	10.4	10.0	9.6
	20 + 20 + 60	1.86	1.86	5.58	-	1.6	9.3	9.6	370	2250	3120	10.4	10.0	9.6
	20 + 25 + 25	2.46	3.07	3.07	-	1.6	8.6	9.6	370	2060	3120	9.6	9.1	8.8
	20 + 25 + 35	2.33	2.91	4.07	-	1.6	9.3	9.6	370	2250	3120	10.4	10.0	9.6
	20 + 25 + 50	1.96	2.45	4.89	-	1.6	9.3	9.6	370	2250	3120	10.4	10.0	9.6
	20 + 25 + 60	1.77	2.21	5.31	-	1.6	9.3	9.6	370	2250	3120	10.4	10.0	9.6
	20 + 35 + 35	2.07	3.62	3.62	-	1.6	9.3	9.6	370	2250	3120	10.4	10.0	9.6
	20 + 35 + 50	1.77	3.10	4.43	-	1.6	9.3	9.6	370	2250	3120	10.4	10.0	9.6
	20 + 35 + 60	1.62	2.83	4.85	-	1.6	9.3	9.6	370	2250	3120	10.4	10.0	9.6
	20 + 50 + 50	1.55	3.88	3.88	-	1.6	9.3	9.6	370	2250	3120	10.4	10.0	9.6
	20 + 50 + 60	1.43	3.58	4.29	-	1.6	9.3	9.6	370	2250	3120	10.4	10.0	9.6
	25 + 25 + 25	2.87	2.87	2.87	-	1.6	8.6	9.6	370	2060	3120	9.6	9.1	8.8
	25 + 25 + 35	2.74	2.74	3.83	-	1.6	9.3	9.6	370	2250	3120	10.4	10.0	9.6
	25 + 25 + 50	2.33	2.33	4.65	-	1.6	9.3	9.6	370	2250	3120	10.4	10.0	9.6
	25 + 25 + 60	2.11	2.11	5.07	-	1.6	9.3	9.6	370	2250	3120	10.4	10.0	9.6
	25 + 35 + 35	2.45	3.43	3.43	-	1.6	9.3	9.6	370	2250	3120	10.4	10.0	9.6
	25 + 35 + 50	2.11	2.96	4.23	-	1.6	9.3	9.6	370	2250	3120	10.4	10.0	9.6
	25 + 35 + 60	1.94	2.71	4.65	-	1.6	9.3	9.6	370	2250	3120	10.4	10.0	9.6
	25 + 50 + 50	1.86	3.72	3.72	-	1.6	9.3	9.6	370	2250	3120	10.4	10.0	9.6
	25 + 50 + 60	1.72	3.44	4.13	-	1.6	9.3	9.6	370	2250	3120	10.4	10.0	9.6
	35 + 35 + 35	3.10	3.10	3.10	-	1.6	9.3	9.6	370	2250	3120	10.4	10.0	9.6
	35 + 35 + 50	2.71	2.71	3.88	-	1.6	9.3	9.6	370	2250	3120	10.4	10.0	9.6
	35 + 35 + 60	2.50	2.50	4.29	-	1.6	9.3	9.6	370	2250	3120	10.4	10.0	9.6
	35 + 50 + 50	2.41	3.44	3.44	-	1.6	9.3	9.6	370	2250	3120	10.4	10.0	9.6

Met 4 units op  
volgende pagina!

# Capaciteitstabel SCM 80 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Uitsluitend in combinatie met SRK xxx ZSX-W

Indoor unit combination		Heating capacity (kW)							Power consumption (W)			Standard current (A)		
		Indoor unit capacity (kW)				Total capacity (kW)			Min.	Standard	Max.	220V	230V	240V
		A	B	C	D	Min.	Standard	max.						
4 units	20 + 20 + 20 + 20	2.33	2.33	2.33	2.33	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	20 + 20 + 20 + 25	2.19	2.19	2.19	2.74	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	20 + 20 + 20 + 35	1.96	1.96	1.96	3.43	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	20 + 20 + 20 + 50	1.69	1.69	1.69	4.23	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	20 + 20 + 20 + 60	1.55	1.55	1.55	4.65	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	20 + 20 + 25 + 25	2.07	2.07	2.58	2.58	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	20 + 20 + 25 + 35	1.86	1.86	2.33	3.26	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	20 + 20 + 25 + 50	1.62	1.62	2.02	4.04	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	20 + 20 + 25 + 60	1.49	1.49	1.86	4.46	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	20 + 20 + 35 + 35	1.69	1.69	2.96	2.96	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	20 + 20 + 35 + 50	1.49	1.49	2.60	3.72	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	20 + 20 + 35 + 60	1.38	1.38	2.41	4.13	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	20 + 25 + 25 + 25	1.96	2.45	2.45	2.45	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	20 + 25 + 25 + 35	1.77	2.21	2.21	3.10	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	20 + 25 + 25 + 50	1.55	1.94	1.94	3.88	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	20 + 25 + 25 + 60	1.43	1.79	1.79	4.29	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	20 + 25 + 35 + 35	1.62	2.02	2.83	2.83	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	20 + 25 + 35 + 50	1.43	1.79	2.50	3.58	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	20 + 35 + 35 + 35	1.49	2.60	2.60	2.60	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	25 + 25 + 25 + 25	2.33	2.33	2.33	2.33	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	25 + 25 + 25 + 35	2.11	2.11	2.11	2.96	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	25 + 25 + 25 + 50	1.86	1.86	1.86	3.72	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	25 + 25 + 25 + 60	1.72	1.72	1.72	4.13	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	25 + 25 + 35 + 35	1.94	1.94	2.71	2.71	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	25 + 25 + 35 + 50	1.72	1.72	2.41	3.44	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2
	25 + 35 + 35 + 35	1.79	2.50	2.50	2.50	1.7	9.3	9.8	350	1950	3120	9.0	8.6	8.2

# Combinatietabel

## SCM 80 ZS-W

**STULZ**

CLIMATE. CUSTOMIZED.

Aansluitbare binnendelen

Aantal binnenunits minimaal: 2

Aantal binnenunits maximaal: 4

Maximaal aansluitbare capaciteit: 13,5kW

Uitzonderingen: Geen

	Aansluitbaar
SRK 20 ZS-W	Ja
SRK 25 ZS-W	Ja
SRK 35 ZS-W	Ja
SRK 50 ZS-W	Ja
SRK 20 ZSX-W	Ja
SRK 25 ZSX-W	Ja
SRK 35 ZSX-W	Ja
SRK 50 ZSX-W	Ja
SRK 60 ZSX-W	Ja
SRK 71 ZR-W	Ja
FDTC 25 VH	Ja
FDTC 35 VH	Ja
FDTC 50 VH	Ja
FDTC 60 VH	Ja
FDTC 25 VF	Nee
FDTC 35 VF	Nee
FDTC 50 VF	Nee
FDTC 60 VF	Nee

	Aansluitbaar
SRR 25 ZM-W	Ja
SRR 35 ZM-W	Ja
SRR 50 ZS-W	Ja
SRR 60 ZS-W	Ja
SRR 25 ZM-S	Nee
SRR 35 ZM-S	Nee
SRR 50 ZM-S	Nee
SRR 60 ZM-S	Nee
FDUM 50 VH	Ja
FDE 50 VH	Ja
SRF 25 ZMX-S	Nee
SRF 35 ZMX-S	Nee
SRF 50 ZMX-S	Nee